

Sherwin Industries, Inc.

MILWAUKEE, WISCONSIN ESTABLISHED 1938







HELPING TO MAKE SAFE ROADS AND RUNWAYS

About Sherwin Industries, Inc.

Sherwin Industries, Inc. became a corporation in 1938 and today Sherwin is in its fourth generation of ownership. Sherwin is divided into four divisions; asphalt and sealcoat manufacturing, distribution of pavement maintenance products, airport runway support, and airfield marking installation. Sherwin has added many different products to our catalog over the years, and continue to look for dependable and reliable items and services to offer our customers. Sherwin is committed to serving our

customers with quality products and excellent customer service. Sherwin has sales offices and dealer locations throughout the continental United States and England to better serve each and every customer.

Sherwin has two locations to better serve our customers; our original office in Milwaukee, WI and our satellite office in Waterford, WI.

Sherwin has been proudly serving County Highway Departments, City DPW's, Towns,



Good Seal Products

A Division of Sherwin Industries, Incorporated

Villages, DOT's, Highway Contractors, Sealcoat Contractors, and Airports for decades.

Sherwin Industries also takes employee satisfaction very seriously. We have several members of our team that have been employed at Sherwin for over 20 years.

From everyone at Sherwin Industries, Inc. we want to thank you for your business, and look forward to working with you for many years to come!






We are proud to be an American Company

TABLE OF CONTENTS











| Contacts | 4 |
|-----------------------|----|
| Office Locations | 5 |
| Warehouse Locations | 6 |
| Rental Equipment | 7 |
| Crafco | 8 |
| Spaulding Mfg., Inc | 27 |
| Trafcon | 28 |
| Ver-Mac | 29 |
| Wanco | 30 |
| Rhino | 32 |
| Graco | 33 |
| Pavement Marking | 45 |
| Airfield Solutions | 50 |
| Personal Safety | 57 |
| Disinfectant Sprayers | 61 |
| Electronic Devices | 62 |
| Traffic Safety | 65 |
| Good Seal | 80 |

Corporate

2129 W. Morgan Ave. Milwaukee WI 53221

Al Schultz, President

aschultz@sherwinindustries.com

Randy Jackson, Vice-President

rjackson@sherwinindustries.com

Brian Krawczyk, Asphalt Plant Manager

bkrawczyk@sherwinindustries.com

Gloria Kurczewski, Inside Sales/Marketing & Website Coordinator

gloria@sherwinindustries.com

Debbie Koss, Office Manager/Accounts Receivable

debbie@sherwinindustries.com

28020 Kramer Rd, Waterford, WI 53185

Matt Smith, Operations Manager msmith@sherwinindustries.com

Ryan Bragg, Technical/Shop Manager rbragg@sherwinindustries.com

Illinois

Jeff Gilmour

jgilmour@sherwinindustries.com Northwest, IL

608-400-1393

Mike West

mwest@sherwinindustries.com
Central and Northeast, IL

309-509-0061

Indiana

Stuart Warner

swarner@sherwinindustries.com

Indiana

574-303-9093

Michigan

Dennis Fleischman

dfleischman@sherwinindustries.com

Western UP

715-531-8119

Nate Luptowski

nluptowski@sherwinindustries.com

Western and Upper Michigan

Eastern UP

989-326-0476

Stuart Warner

swarner@sherwinindustries.com

Lower Michigan

574-303-9093

Keith Zepnick

kzepnick@sherwinindustries.com

Eastern UP

920-894-4184

North Carolina

Eric Reinhardt

ereinhardt@sherwinindustries.com

Western, NC

336-467-2928

Scott Wright

swright@sherwinindustries.com

Eastern, NC

336-312-0656

South Carolina

Eric Reinhardt

ereinhardt@sherwinindustries.com

Western, SC

336-467-2928

Scott Wright

swright@sherwinindustries.com

Eastern, SC

336-312-0656

Virginia

Kevin Doss

kdoss@sherwinindustries.com

804-564-1668

Todd Rushing

trushing@sherwinindustries.com

Airport Runway Support

804-512-2206

Wisconsin

Mike Baier

mbaier@sherwinindustries.com

Southeastern, WI

414-405-6511

Dennis Fleischman

dfleischman@sherwinindustries.com

Northwestern, WI

715-531-8119

Jeff Gilmour

jgilmour@sherwinindustries.com

Southwestern, WI

608-400-1393

Keith Zepnick


kzepnick@sherwinindustries.com

Northeastern, WI


920-894-4184



Phone: 800-525-8876 • Fax: 414-281-6404



WAREHOUSE LOCATIONS



RENTAL EQUIPMENT

PART # DESCRIPTION

G1007R 500 Gallon Sealer Tank

*G1007 300 Gallon Sealer Tank

*S0062R Crafco Model 30 Pavement Cutter with Electric Clutch

Note: With rental of all pavement cutters (routers) the customer must purchase all

cutters, pins and spacers from renter.

*S0064R Crafco Melter Applicator

*S0068R Trailer Mounted Diesel Hot Box

*S0069R Crafco Patcher II for Mastic One and Tech Crete Material Trailer Mounted with

Diesel Burner

Note: All rentals are plus gas, diesel or propane where required.

***S0072R** Four Ton Capacity Dump Trailer

***S0073R** Hot Air Lance - used for properly cleaning and drying cracks prior to sealing

*S0078R 10 Gallon Mastic Cart

S1701R Rental of Lighted Runway Closure Marker (RCM)

Now available with LED units

Note: All rental equipment must be returned clean and in working order otherwise a service fee for clean up and repair will be charged to the renter. All customers who rent must have liability insurance coverage to rent equipment, and name Sherwin Industries, Inc. as additional insured for full value of rented piece of equipment. Proof of insurance is required; and all customers who rent must sign a rental agreement. Renter must have proper size vehicle and tow equipment to tow rental equipment. Sherwin Industries, Inc. has the right to refuse rental if tow vehicle is not large enough, and correct for towing.

Hand agitated and spray systems available. *Please call for availability on above units.

EZ Series II

High Efficiency Melters — Laying Down the Miles

Crafco E-Z Series II are high-performance melters that are designed, built, and backed for laying down miles of crack sealant. Heated hoses and electronic controls make the E-Z Series II the most productive machines available. Automatic electronic controls and modular design features add to the safety and usability of these fourth generation Crafco melters.

The two inch rugged sealant pump with true on demand pumping give the Series II the ability to apply hot pour and fiber sealants quickly and efficiently.

EZ SERIES II 1000

Available in four base configurations

Standard Base (non electric hose) — Part No. 46200SB Standard Compressor — Part No. 47600SC100 Electric Base (electric hose) — Part No. 46200EB Electric Compressor — Part No. 47600EC100

The EZ Series II 1000 has a 2" sealant pump, corrosive resistant tank jacket, two part epoxy paint and one piece frame construction.



EZ SERIES II 1500

Available in six base configurations

Standard Base (non electric hose) — Part No. 46400SB Standard Compressor — Part No. 47800SC100

Electric Compressor — Part No. 47800EC100

Electric Base (electric hose) — Part No. 46400EB

Double Pump Standard Base (non electric hose) —

Part No. 46500SB

Double Pump Electric (electric hose) — Part No. 46500EB

The EZ Series II 1500 is available in a single hose configuration or the first truly

independent twin hose system. The twin hose unit features separate controls, two jacketed pumps, two hoses, two hose booms and two wands that all work independently.



Super Shot Melter Applicators

Engineered Performance for Municipalities and Small Contractors

Simple to start up and shut down, Crafco Super Shot melters are compact units that are suitable for many situations, including local roads and parking lots. Super Shot melters are the ideal, safety-first choice when a contractor or agency is ready to up and do away with pour cones and material handlers. Super Shot machines are some of the safest and easiest to operate of the Crafco line of melters.

Super Shot 60

Available in four base configurations

Skid Mount — Propane — Part No. 50750 Trailer — Propane — Part No. 43300 Skid Mount — Diesel — Part No. 46800 Trailer — Diesel — Part No. 46950

The Super Shot 60 is a 60-gallon capacity unit, which features automatic digital controls with a heated hose and wand. This machine is designed for use on projects under 2,000 pounds of sealant per day. The Super Shot 60 is also available as a skid mount.



Super Shot 125

Available in four base configurations

Skid Mount — Part No. 57200

Trailer — Part No. 43600

Trailer + two axles — Part No. 43600DX

Trailer + compressor — Part No. 47400

The mid-sized 125-gallon capacity Super Shot 125, offers the best versatility. Ideal for medium to large sized projects, this unit is diesel powered, available with an optional compressor or a labor saving autoloader. This is the most popular municipal unit.



Super Shot 250

Available in two base configurations

Trailer — Part No. 44100 Trailer + compressor — Part No. 47900N

The large-sized 250-gallon Super Shot 250 is designed for large projects. This machine will outperform any melter in its class and is available with many standard options.



Engineered Performance Features



QUICK AND EASY START-UP

With the flip of a toggle switch the Super Shot will be ready to operate in less than an hour. Shut down at the end of the day is just as easy.

HEATED HOSE

The low voltage electric heated hose heats material to application temperature within 45 minutes. The hose has the longest working radius in the industry, a 360° swivel, protected sleeve, and a repairable hose and wand.





Automatic Agitator Shut-Off and Splash Proof Lid

Shut offs are incorporated into the lid, hose, wand, pump, burner, and electrical controls.



Integrated Operator Control System

Controls operate the entire unit and overrides possible operator error. Integrated control box houses all the gauges, switches, and engine.



Optional Compressor

Compressor runs air lance used to clean out dirt and debris from cracks increasing crack sealing efficiency.



Optional Engine Cover

Protects engine from the elements, vandalism and theft.



Efficient Burner

Burner is positioned safely within the frame giving it protection and ample ground clearance. Time saving electric overnight pre-heater option available.



Low Profile

Low center of gravity provides easy loading, yet has ample unobstructed ground clearance for safe towing over the most rugged road conditions.

Engineered Performance Options

Crafco offers many Engineered Performance Options to increase production, save labor and lower operating costs. The versatility of the Super Shot units allows you to specify options in your time frame, from the initial placement of the order all the way through production. Most Super Shot units have been engineered to accept any option, whether it's an autoloader, compressor, light bar or fire extinguisher. These options will enhance production, increase safety and security.

Engine covers and battery boxes protect the engine from the elements and add security. The autoloader increases production, adds safety and decreases operator fatigue. The overnight heater is an on the job must if you want to reduce start up time. The light bar is essential for added safety to direct traffic and increase driver awareness. No other machine comes as complete or as diversified.





- Engine Cover
- · Gravity Feed
- Arrow Board Kit
- Surge Brakes
- Engine w/ gauges
- Autoloader
- Custom Paint
- Hitch Selection
- Electric Plug Selection
- Hitch Extension
- Cab Brake Control
- · Locking Battery Box
- · Light Bar
- Overnight Heater
- Fire Extinguisher 10 or 20 lb
- Tool Box
- Safety Hooks
- Mud Flaps
- Spare Tire Kit

Auto-Loader Conveyor

The New Crafco Auto-Loader conveyor increases production by supplying a continuous flow of sealant to the melter. The unique patented design of the Auto-Loader keeps workers out of traffic for loading operation increasing work safety while minimizing the lifting height. All loading is done from in front of the melter/applicator from the truck bed. The sealant blocks move down a conveyor belt and drop into the tank through a antisplash loading door. The Auto-Loader operates off the existing power system on the melter and installs onto most existing power system on the melter and installs onto most existing melter/applicators. The Crafco Auto-Loader can be ordered as an option on new Crafco Supershot and EZ Series II Melter/applicators.



Model 30 Pavement Cutter

Routing and sealing pavement cracks with a Standard Recessed Band-Aid (or over-band) can increase sealant life by over two-times that of non-routed and sealed cracks and there is no better machine on the market than the Model 30 Router. There are four different pavement Model 30 Router configurations, many options and different cutters to meet your demands and exceed your expectations. The Crafco Pavement Router has been the industry best for thirty years.

Selecting the right router



Model 30 Standard **Pavement Router**

- · 19 Standard features deliver the most effective and productive router available
- · Unmatched crack-following accuracy
- · Design minimizes bucking



Model 30 Self-Propelled Router

- · Reduces worker fatigue by moving the router from one distressed pavement area to another, and it works especially well on roads with inclines or hills
- · Reduces physical strain associated with loading and unloading the router onto a trailer during transport



- · Reduces dust by 96% vs. the
- standard model by emitting only 1.25% average dust opacity
- Meets EPA Visible Emissions Standards
- · Improves worker safety due to less dust, flying debris, and clear
- · Contains the debris path for easier clean-up, saving time and money
- Extends the life of the air filter and engine



Pavement Router with Dust Control

· All available router features on one machine for the most innovative, high-quality router available

More options and features than any other router available











Crack-Vac

Dust Containment System

The Crafco Crack-Vac is the environmentally effective way to remove dirt and debris from cracks dust free.

Air quality is our most important concern. The Crafco Crack-Vac cleans pavement cracks and maintains a clean environment while preserving worker and public safety. The Crack-Vac boom extends in front of the truck cab keeping the worker out of traffic areas. With a filter system that contains particle matter down to ten microns (PM 10), the Crack-Vac complies with the strict air quality standards in effect today. This concept in crack sealing preparation limits workers exposure to dust and improves visibility problems that dust can cause the motoring traffic. If airport F.O.D. (Foreign Object Debris) is a concern, the Crack-Vac is ideal for F.O.D. pick-up and disposal. The Crafco Crack-Vac is environmental friendly, safe and highly efficient.





Features:

- · Truck or trailer mount
- 150 gallon holding tank
- 10 micron filtration system
- · Diesel engine
- 473 c.f.m. vacuum
- "Cab over" boom
- · 2.5" diameter suction wand with quick disconnects
- · Replaceable suction wand wear shoes
- · Blower discharge silencer



TechCrete

The Flexible Solution for Concrete Repair

Crafco **TechCrete** is a hot-applied repair mastic sealant, aesthetically suitable in all concrete pavements, and is used in sealing wide cracks and joints, and repairing a large variety of pavement distresses.

BENEFITS:

- Resists cracking, delamination, and spalling
- · It is flexible
- · Supports heavy loads
- · It is long-lasting with proven service greater than 10 years
- · Improves ride quality
- · Provides a high-friction surface to ensure driver safety
- Easy to install and is generally opened to traffic within an hour
- Waterproofs concrete surfaces and resists commonly used chemicals that can destroy pavement



Mastic One / Mastic One Type 2

Permanent Repair for Distressed Concrete and Asphalt Pavements









Crafco **Mastic One**® is designed for large cracks and distressed surface areas too small for repaving. Ideally used to fill distresses. It is a versatile hot-applied, pourable, self-adhesive ridged asphalt binder containing selected aggregate to ensure good load bearing and skid resistant characteristics. Mastic One is compounded with standard weight aggregate. Meets ASTM Specification D8260 Type I.

- It does not require compaction to achieve 100% density
- · It is flexible and can withstand weather, traffic, and thermal movement
- · It is waterproof and provides an air-tight seal
- · It adheres to both asphalt and concrete surfaces

Crafco **Mastic One® Type 2** is ideally suited for cooler climates; may not be suitable for some applications where pavement temperatures exceed 158° F. Meets ASTM Specification D8260 Type II.

HP Concrete Cold Patch

Crafco HP Concrete Cold Patch is a unique, gray color, cold applied, single component patching material. Use HP to repair potholes, spalls, cracks and other confined voids and distresses over 1 inch wide and greater than ½ inch deep in Portland Cement concrete. It can also be used to repair roads, a, streets, airport pavements, parking lots, bridge and parking decks, sidewalks, walkways and floors. Unlike most other concrete patching materials, no mixing, heating or special installation equipment is required.

- · Works in all weather conditions; wet, cold or hot
- · Approved, used and tested by utilities and states nationwide
- Easy to use bags prevent waste and saves money
- No mixing, mechanical compaction or tacking
- Cost effective with no messy clean-up or time constraints
- · Permanently adheres to concrete
- Perfect for all concrete roads, airports, bridges parking decks, sidewalks
- Patch will not release
- Use at any temperature between 30° and 100° F
- · Open to traffic immediately after compacting
- · No heating, mixing or tacking required



HP High Performance Pavement Repair is specifically engineered to remain somewhat pliable following application. This allows our product to eliminate small voids and crevices through continual compaction. Should you require faster set up times, a light sprinkling of Portland cement or mortar dust prior to compaction will help to speed the curing process.











50lb / 22.7kg Bag Usage Guide

| Repair Area Size | Depth in inches | Total bags needed |
|------------------|-----------------|-------------------|
| | 1" | 0.05 |
| 6" X 6" | 2" | 0.1 |
| | 4" | 0.2 |
| | 6" | 0.3 |
| | 1" | 0.2 |
| 12" X 12" | 2" | 0.4 |
| | 4" | 0.8 |
| | 6" | 1.2 |
| | 1" | 0.8 |
| 24" X 24" | 2" | 1.6 |
| | 4" | 3.2 |
| | 6" | 4.8 |

Patcher

Hot Mastic Sealant Melters



Patcher 4 – 395 gallon

The Crafco Patcher is an oil-jacketed melter specifically designed to melt mastic sealants. The Patcher features digital controls to assure that mastic temperatures are held within specifications at all times. The Patcher has angled and staggered agitation blades which provide superior material agitation and aggregate suspension for a consistent material blend. A 6:1 gear box delivers high torque to eliminate agitation stall when using high-density material. The Patcher is equipped with many safety features, including an automatic shut-off on the lid to prevent injuries during operation. With an array of options — like the heated swivel chute — placing mastic is fast and easy.

FEATURES

- · Diesel-powered
- Digital temperature controls
- · Easy clean-out
- · Safety shut-off lid
- · Curb-side controls
- Designed to handle an array of materials
- · Side burner with tool holder
- Individual fuel systems for each burner with separate fuel filters and shut off valves

OPTIONS

- · Fire extinguisher
- Drag Box
- Heat lance
- · Heated Swivel Chute
- Hitches
- · Light kits



Crafco Drag Boxes for the Patcher II allow fast and easy application of Mastic One and PolyPatch, for various types of longitudinal repairs. It's ideal for repairs that utilize the Patcher II; simply attach and drive down the road along the repair.

It's available in various sizes ranging from 10" to 48" wide to cover distresses such as cold joints, shoulder repairs, and alligator cracks. The Crafco Drag Box provides a consistent and smooth application of hot-applied mastics quickly and easily, making longitudinal repairs fast and efficient!

Loop Detection Sealant

Crafco Loop Detection Sealant is specifically designed to provide total and permanent protection in both concrete and asphalt pavements. Crafco Loop Detection Sealant is a hot-melt, rubberized asphalt sealant material that, when properly applied, forms a resilient and adhesive seal. The Crafco Loop Detector Sealing System will save you time, money and labor while helping eliminate the need for the costly repair or replacement

of failed loop wire systems.



Marker Adhesive

Standard Adhesive PN# 34269

- Meets ASTM D4280 and D4383
- Single component Hot applied
- Uniform blend
- Very workable
- · Highly adhesive
- · Crafco quality

Crafco Flexible Marker Adhesive PN# 34270

- Polymer modified for temperature stability.
- · Applied with standard jacketed melter.
- 30% lighter than conventional filled adhesive.
- Will not settle out in the applicator tank.
- · Re-heatable.
- Flexible to 20°F.(-7°C)
- Faster heat up.
- · Extended life.





Super Sealcoater

Designed for the contractor, the Crafco Super SEALCOATER comes loaded with standard features that are considered options on all other competitive seal coat machines. Quality parts and superior construction make the Super SEALCOATER the machine of choice for everyday rigorous use. Features such as the unbreakable steel tank to the oversize hydraulic system set this unit apart from all the others.

- 550 Gallon Trailer-based model
- · 800 Gallon Trailer-based model
- · 800 Gallon Skid-mounted model

FEATURES AND BENEFITS

- · Swivel hose reel
- · Gauged hydraulic tank reservoir
- Air compressor with 13 hp Honda electric start engine
- Optional 35 gallon water tank connected directly to piping system
- · 10 gauge steel tank
- · 6-foot applicator wand
- Variable and reversible hydraulic speed control




The Geo Composite Advantage

Crafco Geo Composites will effectively seal moisture from concrete or asphalt surfaces while dispersing stress associated with reflective cracking of overlaid pavements.

Easy Fast Installation = Long Lasting Cost Effective Results

The leading Geo Composite membranes since 1982



PavePrep is a high density mastic laminated with a tough woven polyester designed specifically to withstand the loads encountered by highway traffic and stress concentrations at pavement joints and cracks. PavePrep's dense and flexible mastic reduces the tendency for cracks to reflect through the overlay by dispersing the pavement stress.

PavePrep SA (Self Adhesive) comes with a peeland-stick adhesive on the application side and does not require a tackcoat for most surfaces.

GeoTac is a peel-and-stick waterproofing membrane designed specifically as a moisture barrier. GeoTac is high caliper and uses a full modified SBS asphalt mastic applied to a non-woven polyester geotextile.

GeoTac HS is composed of a specifically designed polymer modified asphalt waterproofing membrane adhesive that is bonded to a high strength woven polyester fabric backing.

PavePrep specifications

| Property | Value | Test Method |
|-----------------------------|-------------------------------------|----------------------|
| Cold Flex | No cracking or separation of fabric | ASTM D146 (modified) |
| Tensile Strength (Peak) | 2,000 psi minimum | ASTM D412 (modified) |
| Elongation (@ Peak Tensile) | 10% minimum | ASTM D412 (modified) |
| Weight | 0.8 lbs/sf (3.7 kg/m²) minimum | N/A |
| Density (mastic) | 80 PCF minimum | ASTM D70 |
| Thickness | 0.135 inches typical | ASTM D1777 |
| Thickness Retention | 75% minimum retained after loading | ASTM D395 (modified) |
| Absorption (mastic) | 1% maximum | ASTM D517 |
| Brittleness | Passes | ASTM D517 |
| Softening point (mastic) | 210° F - 230° F (99° - 110° C) | ASTM D36 |



PavePrep SA specifications

| PavePrep SA (Self adhesive | e) eliminates the need for a tack coat for application in most |
|----------------------------|--|

| Property | Value | Test Method |
|-----------------------------|-------------------------------------|----------------------|
| Cold Flex | No cracking or separation of fabric | ASTM D146 (modified) |
| Tensile Strength (Peak) | 2,000 psi minimum | ASTM D412 (modified) |
| Elongation (@ Peak Tensile) | 10% minimum | ASTM D412 (modified) |
| Weight | 0.8 lbs/sf (3.7 kg/m²) minimum | N/A |
| Density (mastic) | 80 PCF (1.28g/cc) minimum | ASTM D70 |
| Thickness | 0.135 inches typical | ASTM D1777 |
| Thickness Retention | 75% minimum retained after loading | ASTM D395 (modified) |
| Absorption (mastic) | 1% maximum | ASTM D517 |
| Brittleness | Passes | ASTM D517 |
| Softening point (mastic) | 210° F - 230° F (99° - 110° C) | ASTM D36 |



Advantages

- · Provides a stress relief layer
- · Significantly reduces reflective cracking
- Lowers pavement maintenance costs
- Easy installation
- · Minimal traffic disruption
- · Reduces further structural deterioration
- Reduces moisture penetration
- · Increases overlay life
- · Waterproofs



GeoTac SPECIFICATIONS

| Property | Value | Test Method | | | | | | | |
|------------------------------------|--|---------------------|--|--|--|--|--|--|--|
| Caliper (thickness) | 0.080 inches | ASTM D1777 | | | | | | | |
| Grab Tensile Strength | 50 (Min.) Lbs/in. Min. | ASTM D4632 | | | | | | | |
| Puncture Resistance | 200 lbs. min. | ASTM E154 | | | | | | | |
| Permeance | 0.10 (MAX) perms | ASTM E96, Method B | | | | | | | |
| Elongation | 50% min. | ASTM D4632 | | | | | | | |
| Pliability (2" Mandrel; 180° Bend) | No cracks in fabric or Rubberized Asphalt | ASTM 146 (modified) | | | | | | | |



GeoTac HS SPECIFICATIONS

| Property | Value | Test Method |
|------------------------------------|-----------------------------------|---------------------|
| Caliper (thickness) | 0.065 inches 220 lb. (968 N) | ASTM D1777 |
| Grab Tensile Strength | 200 lbs. (968 N) min. 300lb.(134) | ASTM D4632 |
| Puncture Resistance | 300 lbs. (1344 N) min. | ASTM E154 |
| Permeance | 0.10 US perms max. | ASTM E96, Method B |
| Elongation | 15% min. | ASTM D4632 |
| Pliability (2" Mandrel; 180° Bend) | Pass at -25° F (-31.7° C) | ASTM 146 (modified) |



CRAFCO, INC.





QWIKSEAL is a peel and stick, modified asphalt compound ideal for sealing cracks, seams around pavement patches and concrete joints. Applying QWIKSEAL is as simple as blowing the pavement making sure the surface is clean and dry, unrolling QWIKSEAL and applying it to the surface. Warm the edges to assure a long lasting bond. Properly installed, QWIKSEAL prevent water intrusion and the deterioration it causes to the pavement. QWIKSEAL is compounded to perform in a wide range of climates and conditions.

Crafco QWIKSEAL is supplied in a preformed continuous strip either 4" or 2 1/2" wide and 50 foot long.





Use the Crafco **QWIKDOTS** system to adhere sign posts, rumble strips, speed bumps, parking bumpers, temporary signs or most anything else to both concrete and asphalt pavements. Crafco QWIKDOTS are pressure sensitive peel and stick modified asphalt adhesive pads.

Available in 6" diameter - 120 per box and 8" diameter - 80 per box.








The Crafco **QWIKSTIX** is a fast and easy way to adhere pavement markers or do small crack repairs. The only tool required is a small torch. Peal back the self release cardboard box and melt just enough to do the job. Single markers or touch up to a crack sealing project are ideal for the QWIKSTIX. QWIKSTIX work equally well on AC or PCCP pavements.





S31004 Crack-Stix in 2 Gal. Pail 1/2" Diameter 150 L.F.

(Note: L.F. means Lineal Feet)



CSX900 TORCH

SCSX900

Torch with trigger start/modified tip

Sealant Selection Guide



| | | | | HE | AT PF | | | AS | тм | | | | Α | AS | нтс |) | F | ed | FA | ٩A | | S | PECIALTY |
|------------------------------------|---|-------------|-----------|----|----------|-----------|------------|---------|-----------------|----------|------------------|------------------|------------------|-----------------|--------------|-------|---|--------|---------|---------------|--------------|---------|-----------------------------------|
| PART NUMBER PRODUCT NAME | | OII CT FIBE | S SKETE S | | | 0690 7795 | D 502 TYPE | 11 8/20 | \$ /\$ <u>\</u> | Mas Type | M33 TYPE (M 173) | M33 TYPE (M 301) | MOS TYPE (M 301) | SONFIED NOW 301 | SS 64 74SH70 | 0001C | , , , , , , , , , | ARKING | 1070700 | LIBERIZE RURE | WATERD. SER | 4DHEG. | OTHER SPECS |
| 34200 - Parking Lot Sealant | ſ | | | Ī | Ī | Ť | Ť | Ť | | T | T | T | Ť | | Γ | | | il | | Ī | T | Ť | |
| 34201 - RoadSaver 201 | | | | | | | | | | | | | | | | | Г | T | ī | T | T | T | |
| 34202 - Parking Lot Sealant Type 1 | | | Г | | | | | | Г | | | | | Г | | Г | | | \top | T | T | T | |
| 34211 - RoadSaver 211 | Т | | | | | | | | | | | | | | | Г | Т | T | T | T | T | T | |
| 34220 - RoadSaver 220 | П | | | | | | | | | | | | | | | | Г | T | T | T | T | T | VIRGIN POLYMER |
| 34221 - RoadSaver 221 | П | | | | | | | | | | | | | | | | Г | | Τ | | T | T | |
| 34222 - RoadSaver 222 | Г | | | | | | | | | | | | | | | | Г | T | T | | T | T | |
| 34231 - RoadSaver 231 | П | | Г | | | | | | П | | | | | Г | | Г | Г | | Τ | | T | T | LOW MODULUS |
| 34232 - Asphalt Rubber Type 2 | Г | | Г | | | | | | Г | | | | | Г | | Г | Г | | ī | | T | T | |
| 34234 - Asphalt Rubber Type 4 | П | | Г | | | | | | П | | | | | Г | | Г | Г | | ī | | T | T | |
| 34240 - Asphalt Rubber Type 1 | П | | | | | | | | Г | | | | | Г | | Г | Г | | ī | | | Т | |
| 34241 - Asphalt Rubber Plus | П | | | | | | | | | | | | | | | Г | Г | | ī | | | T | |
| 34244 - Asphalt Rubber Plus Type 2 | П | | | | | | | | | | | | | | | Г | Г | | | | | Т | |
| 34250 - PolyFiber Type 3 | П | | | | | | | | Г | | | | | | | Г | Г | | | | | T | CRAFCO SPECIFICATION |
| 34251 - PolyFiber Type 4 | | | | | | | | | Г | | | | | Г | | Г | Г | | | | | Т | CRAFCO SPECIFICATION |
| 34500 - High Slope | | | | | | | | | | | | | | | | | | | | | | | CRAFCO SPECIFICATION |
| 34515 - RoadSaver 515 | | | | | | | | | | | | | | | | | | | | | | | |
| 34516 - PolyFlex Type 1 | | | | | | | | | | | | | | | | | | | | | | | CRAFCO SPECIFICATION |
| 34517 - Crafco DF | | | | | | | | | | | | | | | | | Г | | Τ | | | \Box | CRAFCO SPECIFICATION |
| 34518 - PolyFlex Type 2 | | | | | | | | | | | | | | | | | | | | | | | CRAFCO SPECIFICATION |
| 34519 - Fiber Asphalt | | | | | | | | | | | | | | | | | | | | | | | CRAFCO SPECIFICATION |
| 34521 - PolyFlex Type 3 | | | | | | | | | | | | | | | | | | | | | | | CRAFCO SPECIFICATION |
| 34522 - RoadSaver 522 | | | | | | | | | | | | | | | | | Г | | Τ | | | \Box | LOW MODULUS, CRAFCO SPECIFICATION |
| 34524 - Pavement Joint Adhesive | | | | | | | | | | | | | | | | | | | \prod | | | | CRAFCO SPECIFICATION |
| 34526 - PolyFlex Type 4 | | | | | | | | | | | | | | | | | Ĺ | | I | I | $oxed{oxed}$ | I | CRAFCO SPECIFICATION |
| 34532 - SuperFlex | | | | | | | | | | | | | | | | | | | \prod | | \prod | \prod | CRAFCO SPECIFICATION |
| 34533 - SuperFlex HT | | | | | | | | | Ĺ | | | | | | | | | | \perp | | \perp | \perp | CRAFCO SPECIFICATION |
| 34534 - RoadSaver 534 | | | | | | | | | | | | | | | | | | | I | floor | I | floor | LOW TACK |
| 34543 - RoadSaver Low Tack | | | | | | | | | | | | | | | | | | | Ι | I | I | I | CRAFCO SPECIFICATION |
| 34546 - RoadSaver Low Tack Type 2 | | | | | | | | | | | | | | | | | | ı | | | | | CRAFCO SPECIFICATION |

All Crafco Products meet or exceed the specifications listed.

Meltable Packaging

Meltable packaging is an exciting development for boxless, consumable packaging of hot-applied pavement crack and joint sealing products. The package consists of the extremely strong and durable yet quick melting wrap, which contains and protects the sealant material.

Meltable packaging products are much easier to handle and melt much faster than with conventional sealant block configurations. These packages and pallets of product are both weather and water resistant.



PACKAGING DETAILS

Package weight 25 lbs ea. 80 packages per pallet Pallet weight 2000 lbs net





PACKAGING DETAILS Package weigh 30 lbs ea. 65 packages per pallet

Pallet weight 1950 lbs net

- No waste
- Easier handling
- Uses less space
- Less pallet & package weight
 Increases production
- No box recycling
- Uses less man power
- Reduces melt time

HBR-XL Backer Rod

For Use with Hot Applied Sealant

| | | WEIGHT | FEET |
|-----------|--------|---------|---------|
| PART# | SIZE | PER BOX | PER BOX |
| S34616-01 | 3/8" | 15# | 3600 |
| S34617-01 | 1/2" | 15# | 2500 |
| S34618-01 | 5/8" | 15# | 1550 |
| S34615-01 | 7/8" | 15# | 850 |
| S34612-01 | 1" | 15# | 550 |
| S34614-01 | 1 1/4" | 15# | 400 |
| S34610-01 | 1 1/2" | 15# | 552 |
| S34609-01 | 2" | 15# | 360 |

Hand Held Backer Rod Installation Tool for proper depth 1/2", 3/4" or 1" available

HBR Backer Rod

Cold Applied for Silicone Sealant Only

| PART# | SIZE | WEIGHT PER BOX | FEET PER BOX |
|-----------|--------|-------------------|-----------------|
| S34621-01 | 1/4" | 15# | 6400 |
| S34626-01 | 3/8" | 15# | 3600 |
| S34627-01 | 1/2" | 15# | 2500 |
| S34620-01 | 5/8" | 15# | 1550 |
| S34625-01 | 3/4" | 15# | 1100 |
| S34622-01 | 7/8" | 15# | 850 |
| S34623-01 | 1" | 15# | 550 |
| S34624-01 | 1 1/4" | 15# | 400 |
| S34608-01 | 1 1/2" | 15# | 552 |
| S34611-01 | 2" | 15# | 360 |

RoadSaver Silicone Sealant

Self-Leveling / Non-Sag / Low Modulus

Crafco RoadSaver Silicone sealants are uniquely formulated, low-modulus sealants produced for sealing joints in Portland cement concrete pavements. The sealants are supplied as single-component, moisture-curing materials which provide lasting weather-resistant, flexible seals. Crafco hot-applied asphaltic sealant demonstrated more than 21 years of sealant service life in concrete pavement, the longest ever recorded and published.

Joint Design for Crafco RoadSaver Silicone Sealants in Joints in PCC Pavements Joint Design

| *Join Width | 1/4" | 3/8" | 1/2" | 5/8" | 3/4" | 7/8" | 1" | 1 1/8" | 1 1/4" | 1 3/8" | 1 1/2" |
|--|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Minimum Sealant Recess | 1/4" | 1/4" | 5/16" | 5/16" | 3/8" | 3/8" | 3/8" | 1/2" | 1/2" | 1/2" | 1/2" |
| Backer Rod Diameter ¹ | 3/8" | 1/2" | 5/8" | 3/4" | 7/8" | 1" | 1 1/4" | 1 1/2" | 1 1/2" | 1 34" | 2" |
| Sealant Bead Thickness ^{2,3} | 1/4" | 1/4" | 1/4" | 5/16" | 3/8" | 7/16" | 1/2" | 1/2" | 1/2" | 1/2" | 1/2" |
| Minimum Joint Saw/Reservoir Depth | 1 1/8" | 1 1/4" | 1 1/2" | 1 3/4" | 1 7/8" | 2" | 2 3/8" | 2" | 2 7/8" | 3 1/8" | 3 3/8" |
| Minimum Backer Rod Depth | 1/2" | 1/2" | 5/8" | 11/16" | 3/4" | 13/16" | 7/8" | 1" | 1" | 1" | 1" |
| Estimated Usage Non-Sag (ft/gal) | 245 | 149 | 112 | 70 | 51 | 35 | 26 | 23 | 18 | 16 | 15 |
| Estimated Usage Self-leveling (ft/gal) | 273 | 172 | 130 | 82 | 58 | 41 | 31 | 27 | 22 | 20 | 19 |

- 1 Backer rod diameter should not be varied from specified dimensions. If larger sizes are used, increased saw depth is needed.
- 2 Sealant bead thickness can vary by +25% of design value.
- 3 Never install Roadsaver Silicone to a depth greater than the joint width (1 to1).

RoadSaver Silicone SL (Self-Leveling) Part Number: 34903



RoadSaver Silicone NS (Non-Sag) Part Number: 34902



RoadSaver Silicone SL Ultra-Low Modulus

(Self-Leveling) Part Number: 34904LM



Crafco RoadSaver Silicone is designed to:

- · Keep moisture out of pavement subbase
- · Prevent incompressible items from entering joints
- · Prevent pavement distresses like cracks and spalls
- · Be flexible and durable to work in any climate
- · Withstand weather, traffic, and thermal movement
- · Last longer than other silicone joint sealants



RoadStar & Highway Star

Joint Sealant Pumps



5 Gallon

- German Designed & Engineered
- 38:1, 48:1 or 59:1 Power Ratios
- · Built and Serviced in the U.S.A.
- Chopping Check Style Pump
- 3" Post Double Elevator / Ram
- Air Line Filter / Lubricator / Regulator
- · Applicator Valve or Gun & Wand
- Operating and Service Manual
- 30' Basic Application Hose Tool Kit Available

5 Gallon Pail Conversion Kit Available

55 Gallon Drum Wiper/

Auto Drain Water Separator

One Person Drum Installation

Follower Plate

Hose Support

- 360° Drum Locator / Clamp holds drum in place while traveling. Can be opened right or left for convenience while changing drums.
- Stainless Steel of Zinc Plated external surfaces and fasteners for maximum corrosion protection in outdoor applications.

• Pump fluid section can be rotated 180° for ease of mounting in truck or trailer.




55 Gallon

Matrix Asphaltic Bridge Plug Joint System

Matrix 501: pre-measured, prepackaged blend

Matrix 502: engineered for all climates; field blended



FEATURES:

- * Meets ASTM D6297
- Easy to Install
- · Smooth Ride
- Watertight
- Maintainable
- Premeasured Consistency



Engineered Tools

Sealing Tips and Material Handling Tools



Super Shot Drip Stopper

Use with Crafco Super Shot sealing tip. Stops sealant drip once wand trigger is released. **1** PN# 27114 Tip Adapter

2 PN# 50270 Duckbill Valve

3 PN# 27115 Shroud - Tip Adapter



Swivel Applicator

Use with Super Shot Melter & E-Z Pour Melters with or w/o Drip Stopper. PN# 27120 3" Swivel Applicator PN# 27130 4" Swivel Applicator



Crafco Duckbill PN# 50270

Use with Super Shot Melter wands to prevent dripping of material.



Crafco Sealing Foot / Flush

Used for random asphalt and concrete cracks. PN# 27154 Sealing tip/ft assembly 1/4" flush PN# 27155 Sealing tip/ft assembly 3/8" flush



Crafco Sealing Foot / Protruded

Used for straight asphalt and concrete joints. PN# 27159 Sealing tip/ft assembly 1/4" protruding PN# 27160 Sealing tip/ft assembly

3/8" protruding



Crafco Joint Sealing Tip

Use for straight asphalt and concrete joints. PN# 27146 Sealing tip assembly 1/4" PN# 27147 Sealing tip assembly 3/8"



Crafco Round Sealing Tip

Multi-purpose random cracks and joints. Use with a squeegee for most applications. PN# 27170 Sealing tip assembly 3/8" PN# 27171 Sealing tip assembly 1/2"



Crafco Applicator Disk

Used for overbanding, great labor saver.

PN# 27162 3" Disk Assembly PN# 27163 4" Disk Assembly

PN# 27164 6" Disk Assembly



Use for leveling crack sealant and where a sealant over band is recommended.

Crafco Replacement Blade PN# 27195 4" x 18" x 3/8"



Squeegee w/ Wooden Handle PN# 27245W

Use for leveling crack sealant and where a sealant over band is recommended.

Crafco Replacement Blade PN# 27241 2-1/2" x 17" x 3/8"



Use to apply a uniform band of sealant to a crack or joint. Wheeled for ease of use. Gravity feed with shut off lever.



Crafco Hand Held Pour Pot PN# 40201

For application of thin crack sealant to a joint or crack. Gravity feed with shut off lever.



L.A.B. Torch Hot Air Lance Equipment

S70 Model B Lance Kit w/50' Hose Kit Assembly

S70A Model B Lance Only - No Hose Kit

SWKC Wheel Kit w/Debris Guard

 SHK-40
 40' Hose Kit

 SHK-50
 50' Hose Kit

 SHK-60
 60' Hose Kit

S7139 Hose Sleeve Cover - Replacement

S70C Model C Lance Kit w/50' Hose Kit Assembly

Model B - Classic & Hot Shot

Heated Air Temperatures: 400° F to 2600° F Exit Heated Air: Up to 1000 ft. per second

Propane: 5 to 30 psi

Compressed Air Supply: 60 - 100 cfm, 50- 175 psi (Hot Shot)

Propane Consumption: 10 Lbs per hour @ 20 psi

100-185 cfm, 50 - 175 psi (Classic)



Model C Blaster

Heated Air Temperatures: 600° F to 3000° F Exit Heated Air: Up to 3000 ft. per second

Propane: 5 to 30 psi

Compressed Air Supply: 150 + cfm, 90- 175 psi Propane Consumption: 12 Lbs per hour @ 20 psi

BTU's: To 1,500,000 Lance Weight: 12 Lbs Stainless Steel Construction



Complete Package Includes:

- Hot Air Lance Unit
- Hose Kit Assembly (40', 50', 60') in protective hose cover
- Wheel Kit Debris Guard Optional
- Shoulder Strap

- · Heavy Duty Air Filter
- LP Regulator & Gauge
- Quick Connect Fittings
- · Safety & Operation Manual
- Warranty Card

EZ Mini Melter System

Heat, apply and Detack with Crafco quality products featured in the Crafco EZ Mini Melter System of crack sealing.



The Mini Melter 30 (air jacketed hand agitated) is a 30 gallon sealant melter and dispenser that can be used in conjunction with the Mini Melter 10 or the Crafco Pour Pot with Wheels.

The Mini Melter 10 is a hand agitated, 10 gallon melter/applicator, that will melt sealant for application in approximately twenty minutes. The wheeled melter easily follows random cracks for efficient crack sealing.

The Wheeled Pour Pot is used to apply a uniform band of sealant to a crack or joint. Wheeled for ease of use and ideally used with the Mini Melter 30.

The Mini Melter System is an ideal optional "add on" to the Crafco Super SealCoater.

To double sealant life, rout cracks prior to sealing with the Crafco Pavement Cutter.

Crafco Pour Pot w/ Wheels Part Number 40200 Steel Wheels Part Number 40200W Weld Plates Part Number 40200A

Applies over hot sealant

- Eliminates blotting
- Increases production
- Reduces traffic closures
- Protects sealant integrity
- Eliminates Tracking
- Eliminates sticking
- Decreases labor cost
- Reduces traffic closures

Open traffic immediately after crack sealing by eliminating the "stick" from newly applied hot sealant. **DETACK** is supplied ready to use in 5 gallon (19L) plastic pails. To use, **DETACK** is poured in to typical hand pump pressurized garden sprayers. **DETACK** should be applied to the sealant immediately after sealant is placed, or at any time after sealant is placed when surface tack is present. Usage rate of **DETACK** is typically 1 gallon (3.8L) per 1000-2000 linear feet (305-610m) of sealed cracks. **DETACK** should be applied to cover the sealant surface with minimal excess of application onto the pavement surface.

DETACK (5 gal pail)Part Number 34681



Pave Pro 100% Biodegradable Asphalt Remover - EPA and RCRA Approved

Part No. Container Size

\$86 5 gal pail

S86C 55 gal drum

(available in orange, green

and gold)

S1996VI Pave Pro Funnel Top

2 gallon hand sprayer pump

w/ Viton seals





GREASE OIL ROAD TAR ASPHALT CLEANER



Solvall is a ready-to-use, water-rinsable liquid, which easily removes coal tar sealer, asphalt sealer, crack sealer, roofing tar, mastic, tack coat, or oil and grease from washable surfaces. It can be safely used on tools, equipment, vehicles, sidewalks, flooring, siding, clothing and carpeting. Solvall will clean up fresh spills, splatters and over-sprays, as well as caked-on messes.

Part No. S85 1 gal.,

Part No. S85B 1 qt spray bottle



Paving Equipment Cleaner is a safe, effective substitute for diesel fuel to clean and prevent asphalt build up on tools and equipment. Paving Equipment Cleaner starts to work immediately and is non-toxic, non-hazardous, non-flammable, and non-ozone depleting. In addition, Paving Equipment Cleaner is non-reactive. Part No. S89



Oil-Flo is a specialized product for removing organic stains such as asphalt, tar, oils tree pitch, adhesive stickers, gum, candle wax, silicon caulk, roof tar, oil, etc. It is a versatile and effective cleaner that works especially great for removing graffiti. Oil Flo is safely used on glass, vinyl, concrete, metals, carpets and clothing. Oil Flo is the proven answer to cleaning asphalt, spills, overspray, equipment, clothes, and concrete. Non-volatile.

Part No. S85A 1 gal.

Hot Patchers

Spaulding Manufacturing, Inc. is a company that excels in Road Maintenance Equipment.

Features & Options:

- Trailer
- · Chassis Mount
- Slip-In
- · Hook lift

Hopper Style Options:

· Oil Jacket or Air Jacket

Heat Sources:

· Diesel or Propane

Capacity:

• 1-4 Ton, 6 Ton and 8 Ton

Features:

- · Triple Wall Hopper Construction
- · High Temperature Hopper Insulation
- Heavy Duty Frame Construction 6x2x5/16
- Manual Top Doors
- · Single Manual Guillotine Style Rear Unloading Door
- · Designed for Easy Loading with Pay loader or at the Asphalt Plant
- · Rear curbside Control Operation with Automatic Temperature Control and Zone Heating
- · Easy Clean Out at End of Day
- · Replaceable Flue which makes for easy maintenance and extends the life of the unit
- · Outer Skin of hopper made out of 12 gauge material
- · Inner skin of hopper made out of 10 gauge material

Options:

- · Hydraulic Dumping Hopper
- · Safety Lighting: Strobes, Arrow Stick, Work lights, mini strobes, etc.
- · Electric Overnight Heating 110v or 220v
- · Heated Tack Tank
- Spray System for Tack Tank
- Solvent Tank for Shovels
- · 5 Piece Tool Holder
- · Tool Box for Small Hand Tools
- · Fire Extinguisher with Bracket
- · Hydraulic Tamper Lift
- · Basket for Tamper Plate or Bulldog Roller
- · Hydraulic Rear Door
- · Hydraulic Top Doors
- · Wheel Chocks
- · Propane Torch
- · Bulldog 500 Roller
- Spare Tire with Bracket
- · Wheel Chocks
- · Surge Brakes
- · Hoist for lifting carts or propane tanks
- · Cold Weather Package 12vdc Fuel Heater
- · Mounted 30cfm gas operated air compressor
- · Marine Style Battery Charge



4 Ton Oil Jacketed w/Dump Box, Tack Tank, Spray System and Hydraulic Tamper Lift





Bulldog 500 Roller



Features:

- Vibratory Action
- · Honda Engine Compacts at 850psi
- · Adjustable Handle
- · Front & Rear Spring Loaded Scaper Bar
- · Built-in Rust Proof Tank
- · Water bar over Drum
- · Lightweight at 108 lbs.

Benefits:

- · Easy loading and offloading to trailer
- · Permanent compaction for small asphalt repair
- Easy maneuverability to repair site

Arrow Boards, Portable Changeable Message Signs and Speed Display Trailers

Arrow Board - Trailer Mount

TC: models are trailer-mounted and come in your choice of base model, or an upgraded version.



Speed Display Trailer

SST model represents the ultimate traffic calming device combining the flexibility of modular message sign system together with a portable, light-weight trailer.



Arrow Board - Vehicle Mount

MB Models are vehicle mounted and come in your choice of panel size, lamp and mount types.



Portable Changeable Message Sign - Trailer Mount

TC1-ADS models are solar-powered trailer-mounted dynamic message signs that combine the convenience of an arrow board with the flexibility of a dynamic message sign. The result is a complete family of signs designed to fit any application.





MB-ADS models combine the flexibility of real-time, dynamic messaging with complete mobility. The result is a family of signs with a universal mounting system designed for trucks and vans that can be customized for a wide range of vehicle makes and styles.

Contact us for additional information on the above

Portable Message Boards - Trailer Mounted

PCMS-1210

3-Line Portable Changeable Message Sign PRO Series — Large Size 75 x 132 in. (1917 x 3343 mm) NTCIP Compliant V-Touch Controller





PCMS-1500

Full-Matrix Portable Changeable Message Sign PRO Series — Large Size 75 x 131 in. (1917 x 3331 mm) 28 x 48 pixels NTCIP Compliant V-Touch Controller



Full-Matrix Portable Changeable Message Sign Mid Size 64 x 105 in. (1625 x 2667 mm) 30 x 48 pixels NTCIP Compliant V-Touch Controller





PCMS-320RT

Full-Matrix Portable Changeable Message Sign Mid Size 65 x 105 in. (1680 x 2667 mm) 30 x 48 pixels Rainbow Technology 16,000 Colors NTCIP Compliant V-Touch Controller

Other options available upon request

Variable Message Signs



Color Message Signs

Five-color matrix display allows you to display bold messages with text, graphics or a combination of both. Includes software for creating custom messages.



Matrix Message Signs

Ideal for large roadwork projects, public events and more, these full-size signs feature a large display, exceptional visibility and versatility. Meets MUTCD.



Three-Line Message Signs

Perfect for simple text messages in one, two or three lines of eight characters or less. Select from programmed messages or create your own. Meets MUTCD.

Truck Mount Signs

Full-matrix signs in two sizes for text and graphical messages. A touchscreen controller inside the cab provides easy access to control the message sign.



Arrow Boards and Radar Speed Signs

Truck Mounted Arrow Boards

Perfect for convoys, crash-cushion (TMA) trucks and emergency repair crews. Four sizes of arrow boards and the largest selection of mounting options.



Folding Frame Arrow Boards

A single support holds the display panel during use and during transport. This unique design eliminates abrasion, extending the arrow board's useful lifespan.



Folding Frame Radar-Speed Trailers

Perfect for highways and roadwork zones, our folding-frame trailers hold two large regulatory signs, and their speed display can be seen over a Jersey barrier.



Pole-Mount Radar-Speed Signs

Our pole-mount signs can be hard-wired to commercial power or battery-powered with an automatic solar charging system. Choose from two display sizes.



Contact us for additional information on the above



Maximize your profits with Rhino Tool Company's Gas powered or Air Operated Post Drivers and Manual or Hydraulic Post Pullers.



Post Drivers

Easily operated by one person and is the perfect choice for driving all types of steel posts!

Drivers are fast, safe, portable, and will increase productivity while reducing costs!

Models:

- PD-55
- PD-55 Postmaster
- PD-110
- PD-140
- PD-140S

- PD-200
- PD-200 Pile Driver Kit
- PD-200G
- PD-200S











Post Pullers

Post Pullers are offered in hydraulic and manual models.

Pullers are self-contained, safe, portable, can be operated by one person and offer 3 tons of force!

Models:

- MP-3 (Manual)
- PL-3 (Hydraulic)



Rhino® Ranch Pro™

- · Gas Powered Driver
- Perfect choice for T-post and Ground Rod
- 1¾" ID heavy wall chuck with a 1" adapter and locking clip for the toughest applications
- Powerful yet lightweight and ergonomic
- Rhino's CIS™ Vibration Dampening



GRACO Genuine Parts & Authorized Service

LineLazer Battery Powered Series

| | EFULLE LITTERING | EPONEI LITTRIUM | EPONIAN LITHIUM | | | | | | | | | | |
|----------------------------|-----------------------|--|-----------------------|---|--------------------------|--|--------------------|--|--|--|--|--|--|
| | LINELAZER ES500 | LINELAZER ES1000 | LINELAZER V ES2000 | | | | | | | | | | |
| Honda GX Engine cc (hp) | N/A | N/A | N/A | | | | | | | | | | |
| | 0 | | | | | | | | | | | | |
| SERIES TYPE | STANDARD | STANDARD | STANDARD | | HP AUT | OMATIC | | | | | | | |
| Part Number | 25U546 | 25U674 – 1 Battery 25U676 – 2 Battery | 25U678 – 2 Battery | 25U679 – 2 Battery | 25U680 – 2 Battery | 25U683 – 2 Battery | 25U684 – 2 Battery | | | | | | |
| Gun(s) | Flex Plus 2 Manual | Flex Plus 2 Manual | Flex Plus 2 Manual | Flex Plus 1 Automatic, 1 Manual | Flex Plus 2 Automatic | Flex Plus 1 Automatic, 1 Manual Flex Plus 2 Automatic | | | | | | | |
| Laser | | | | | LazerGuide 1700 | Start/Stop Laser | | | | | | | |
| Laser | | | | LazerGuide 2000 Laser-Guided Layout System | | | | | | | | | |

LineLazer Series

| | LINELAZER 3400 | LINELAZER 130HS | LINELAZER V 3900 | | | | |
|----------------------------|-------------------|--------------------|-----------------------|---------------------------------------|--------------------------|---------------------------------------|---------------------------|
| Honda GX Engine cc (hp) | 120 (4.0) | 120 (4.0) | 120 (4.0) | | | | |
| | 0 | | | | | | |
| SERIES TYPE | STANDARD | STANDARD | STANDARD | HP AUTOMATIC | | | |
| Part Number | 25M224 | 17H448 | 17H450 | 17H452 | 17H453 | 17U804 | 17U805 |
| Gun(s) | Flex Plus | Flex Plus | Flex Plus 2 Manual | Flex Plus 1 Automatic, 1 Manual | Flex Plus 2 Automatic | Flex Plus 1 Automatic, 1 Manual | Flex Plus 2 Automatic |
| Laser | | | | LazerGuide 1700 Start/Stop Laser | | | |
| Laser | | | | | | | ide 2000 Layout System |

GRACO Genuine Parts & Authorized Service

LineLazer Series


| | LINELAZER V 5900 | | | | LINELAZER V 200HS | | | | |
|----------------------------|-----------------------|---------------------------------------|---|---------------------------------------|--------------------------|-----------------------|---------------------------------------|--------------------------|--|
| Honda GX Engine cc (hp) | 160 (5.5) | | | | | 200 (6.5) | | | |
| | | | | | | | | | |
| SERIES TYPE | STANDARD | HP AUTOMATIC | | | STANDARD | HP AUT | OMATIC | HP REFLECTIVE | |
| Part Number | 17H455 | 17H457 | 17H458 | 17U802 | 17U803 | 17H461 | 17H463 | 17H464 | 17H465 |
| Gun(s) | Flex Plus 2 Manual | Flex Plus 1 Automatic, 1 Manual | Flex Plus 2 Automatic | Flex Plus 1 Automatic, 1 Manual | Flex Plus 2 Automatic | Flex Plus 2 Manual | Flex Plus 1 Automatic, 1 Manual | Flex Plus 2 Automatic | Flex Plus 2 Automatic, PBS INSTALLED 1 TANK |
| Laser | | LazerGuide 1700 Start/Stop Laser | | | | LazerG | uide 1700 Start | /Stop Laser | |
| Laser | | | LazerGuide 2000 Laser-Guided Layout System | | | | | | |

| | LINELAZER V 200DC | | | LINELAZER V 250SPS | | | | |
|----------------------------|-----------------------|----------------------------------|--|--|--|---|--|---|
| Honda GX Engine cc (hp) | 200 (6.5) | | | 390 (13.0) Electric Start | | | | |
| | | | | | | | | |
| SERIES TYPE | STANDARD | HP AUTOMATIC | HP REFLECTIVE | HP AUTOMATIC | HP REFLECTIVE | | | |
| Part Number | 17Y231 | 17Y269 | 17Y270 | Honda - 17H467 | Honda - 17J951 | Honda - 17H469 | Honda - 25D345 | Honda - 25D340 |
| | | | | 17H467V - Vanguard (CARB Approved) | 17J951V - Vanguard (CARB Approved) | | 25D345V - Vanguard (CARB Approved) | |
| Gun(s) | Flex Plus 2 Manual | Flex Plus 2 Automatic | Flex Plus 2 Automatic, PBS INSTALLED 1 TANK | Flex Plus 2 Automatic | Flex Plus 2 Automatic, PBS INSTALLED 1 TANK | Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS | Flex Plus 2 Automatic, PBS INSTALLED 1 TANK | Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS |
| Laser | | LazerGuide 1700 Start/Stop Laser | | | | | | |
| Laser | | | | | | | LazerGuide 3000 | Long-Line Laser |

LineLazer Series

| | LINELAZER V 250DC | | | | | | | |
|----------------------------|--|--------------------------|---|---|---|---|--|--|
| Honda GX Engine cc (hp) | 390 (13.0) Electric Start | | | | | | | |
| | | | | | | | | |
| SERIES TYPE | HP AUT | OMATIC | HP REFLECTIVE | | | | | |
| Part Number | Honda - 17H471 | Honda - 17H472 | Honda - 17H473 | Honda - 17H474 | Honda - 25D343 | Honda - 25D344 | | |
| | 17H471V - Vanguard (CARB Approved) | | | 17H474V - Vanguard (CARB Approved) | | 25D344V - Vanguard (CARB Approved) | | |
| Gun(s) | Flex Plus 2 Automatic | Flex Plus 3 Automatic | Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS | Flex Plus 3 Automatic, PBS INSTALLED 2 TANKS | Flex Plus 2 Automatic, PBS INSTALLED 2 TANKS | Flex Plus 3 Automatic, PBS INSTALLED 2 TANKS | | |
| Laser | | | | | | | | |
| Laser | | | | | LazerGuide 3000 | Long-Line Laser | | |

| | LINELAZER V 200MMA 1:1 | | | | |
|-------------|------------------------|-------------|--|--|--|
| | | | | | |
| SERIES TYPE | HP REF | LECTIVE | | | |
| Part Number | 17Y271 | 17Y512 | | | |
| Gun(s) | 1 Automatic | 2 Automatic | | | |



| | FIELDLAZER \$100 | FIELDLAZER ES100 | | |
|-------------|---------------------------|---------------------------|--|--|
| | 8 | 8 | | |
| | | | | |
| Part Number | 248942 | 25U542 | | |
| Power | Honda GX | Battery Powered | | |
| Features | High-Pressure, Airless | High-Pressure, Airless | | |



GRACO Genuine Parts & Authorized Service

LazerGuide 2000

The LazerGuide 2000 LaserGuided Layout System eliminates tedious manual layout work while producing laser quality lines every time.





Requires a string line, chalk and 2 people




Lazer-Guide 2000 Laser-**Guided Layout System** No string line, no chalk and 1 person

Traditional Method

Features

- Higher productivity No more wasting time laying out parking lots with strings, measures and chalk
- Less labor Stripe parking lots with just one person
- Less fatigue No more kneeling down to place and move string lines or measuring tapes
- Simple operation Just line it up with the target box and go
- · Accurate Once lined up you are assured straight lines every time even in windy conditions



LINELAZER V 5900 HP AUTOMATIC 17U803 Two auto guns with new LazerGuide 2000 Laser-Guided **Layout System**



ThermoLazer Series







| | 1 | | | |
|-----------------------------------|---|--------------------------|----------------------------|--|
| UNIT MODEL THERMOLAZER 200TC SYS | | THERMOLAZER 300TC SYSTEM | THERMOLAZER PROMELT SYSTEM | |
| Melt Chamber Capacity Lb (Kg) | amber Capacity Lb (Kg) 200 (91) 300 (136) | | 300 (136) | |
| Melt Time (300 lbs w/o Premelter) | Up To 2.5 Hours | Up To 4.5 Hours | 1 To 1.5 Hours | |
| Material Mixing | Corkscrew Auger | Dual-Paddle | Quad Mix | |
| Weight 260 (118) | | 295 (133) | 345 (157) | |
| Linedriver Compatible No | | Yes | Yes | |

| Direct Burners 475°F Direct Burners Direct Burners Direct Burners 475°F Direct Burners Direct Burners Direct Burners Direct Burners Direct Burners Direct Burners 2475°F Direct Burners Direct Burners Direct Burners Direct Burners 2475°F Direct Burners 2475°F Direct Burners 2476°F 24864 | Fuel Source | LP Gas (LP Tank NOT Included) | LP Gas (LP Tank NOT Included) | LP Gas (LP Tank NOT Included) | |
|---|---------------------------------------|-------------------------------|-------------------------------|-------------------------------|--|
| Sead Hopper Capacity Lb (Kg) | Main Burner BTU | 30,000 BTU Single | 30,000 BTU Dual | 100,000 BTU Dual | |
| Seed Hopper Capacity Lb (Kg) | Die Heat System | Direct Burners | Direct Burners | Direct Burners | |
| SmartDie II | Temperature Limit Control | N/A | N/A | 475°F | |
| SmartDie II | | | | I | |
| Bare Unit (No Die) 24U281 24H622 24H624 (Thermolazer w/Die 2 in (5 cm) 17A332 18B403 17B187 3 in (8 cm) 17A333 18B404 24R761 4 in (10 cm) 24U282 258699 24H623 4.75 in (12 cm) - 18B406 18B400 5 in (13 cm) 17A334 18B407 24R762 6 in (15 cm) 17A335 18B408 24R763 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B410 24R765 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 x 13 cm) - 18B419* 18B401* | | 40 (18) | ` ' | , , | |
| Thermolazer w/Die 2 in (5 cm) 17A332 18B403 17B187 3 in (8 cm) 17A333 18B404 24R761 4 in (10 cm) 24U282 258699 24H623 4.75 in (12 cm) - 18B406 18B400 5 in (13 cm) 17A334 18B407 24R762 6 in (15 cm) 17A335 18B408 24R763 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B400 24R764 8 in (20 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R770 4 x 4 x 4 in (10 x 10 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B401* 18B401 24R762* 18B401* | Compatible Dies | FlexDie | SmartDie II | SmartDie II | |
| Thermolazer w/Die 2 in (5 cm) 17A332 18B403 17B187 3 in (8 cm) 17A333 18B404 24R761 4 in (10 cm) 24U282 258699 24H623 4.75 in (12 cm) - 18B406 18B400 5 in (13 cm) 17A334 18B407 24R762 6 in (15 cm) 17A335 18B408 24R763 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B400 24R764 8 in (20 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R770 4 x 4 x 4 in (10 x 10 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B401* 18B401 24R762* 18B401* | Bare Unit (No Die) | 24U281 | 24H622 | 24H624 | |
| 3 in (8 cm) 17A333 18B404 24R761 4 in (10 cm) 24U282 258699 24H623 4.75 in (12 cm) - 18B406 18B400 5 in (13 cm) 17A334 18B407 24R762 6 in (15 cm) 17A335 18B408 24R763 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B410 24R765 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 x 13 cm) - 18B419* 18B401* | Thermolazer w/Die | | | | |
| 4 in (10 cm) 24U282 258699 24H623 4.75 in (12 cm) - 18B406 18B400 5 in (13 cm) 17A334 18B407 24R762 6 in (15 cm) 17A335 18B408 24R763 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B410 24R765 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R72* 5 x 5 x 5 in (13 x 13 x 13 x 13 cm) - 18B419* 18B401* | 2 in (5 cm) | 17A332 | 18B403 | 17B187 | |
| 4.75 in (12 cm) - 18B406 18B400 5 in (13 cm) 17A334 18B407 24R762 6 in (15 cm) 17A335 18B408 24R763 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B410 24R765 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17A344 18B416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 3 in (8 cm) | 17A333 | 18B404 | 24R761 | |
| 5 in (13 cm) 17A334 18B407 24R762 6 in (15 cm) 17A335 18B408 24R763 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B410 24R765 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17A342 18b416 24r70 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 4 in (10 cm) | 24U282 | 258699 | 24H623 | |
| 6 in (15 cm) 17A335 18B408 24R763 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B410 24R765 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 4.75 in (12 cm) | - | 18B406 | 18B400 | |
| 7 in (18 cm) 17A336 18B409 24R764 8 in (20 cm) 17A337 18B410 24R765 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D758* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 10 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 5 in (13 cm) | 17A334 | 18B407 | 24R762 | |
| 8 in (20 cm) 17A337 18B410 24R765 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 x m) - 18B419* 18B401* | 6 in (15 cm) | 17A335 | 18B408 | 24R763 | |
| 9 in (22.5 cm) 17A338 18B411 24R766 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17A342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 7 in (18 cm) | 17A336 | 18B409 | 24R764 | |
| 10 in (25 cm) 17A339 18B412 24R767 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 8 in (20 cm) | 17A337 | 18B410 | 24R765 | |
| 12 in (30 cm) 17A340 18B413 24R768 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 9 in (22.5 cm) | 17A338 | 18B411 | 24R766 | |
| 16 in (41 cm) - 18B414* 17B188* 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 10 in (25 cm) | 17A339 | 18B412 | 24R767 | |
| 18 in (46 cm) 26D757* 26D758* 26D759* 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 12 in (30 cm) | 17A340 | 18B413 | 24R768 | |
| 3 x 3 x 3 in (8 x 8 x 8 cm) 17A341 18B415 24R769 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 16 in (41 cm) | - | 18B414* | 17B188* | |
| 4 x 3 x 4 in (10 x 8 x 10 cm) 17a342 18b416 24r770 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 18 in (46 cm) | 26D757* | 26D758* | 26D759* | |
| 4 x 4 x 4 in (10 x 10 x 10 cm) 17A344 18B417 24R771 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 3 x 3 x 3 in (8 x 8 x 8 cm) | 17A341 | 18B415 | 24R769 | |
| 4 x 6 x 4 in (10 x 15 x 10 cm) - 18B418* 24R772* 5 x 5 x 5 in (13 x 13 x 13 cm) - 18B419* 18B401* | 4 x 3 x 4 in (10 x 8 x 10 cm) | 17a342 | 18b416 | 24r770 | |
| 5 x 5 x 5 in (13 x 13 x 13 cm) – 18B419* 18B401* | 4 x 4 x 4 in (10 x 10 x 10 cm) | 17A344 | 18B417 | 24R771 | |
| ` ' | 4 x 6 x 4 in (10 x 15 x 10 cm) | - | 18B418* | 24R772* | |
| 6 x 3 x 6 in (15 x 8 x 15 cm) 26D756* 18B420* 18B402* | 5 x 5 x 5 in (13 x 13 x 13 cm) | - | 18B419* | 18B401* | |
| | 6 x 3 x 6 in (15 x 8 x 15 cm) 26D756* | | 18B420* | 18B402* | |

^{*}Bead dispenser kit larger than 12 in recommended (see Thermolazer Accessories)

RoadLazer RoadPak

20 READY-TO-STRIPE SYSTEMS

Select the right preconfigured system for your jobs — now and in the future. With the modular design of the RoadPak System, you can be assured of fast installation of your new striping system. Plus, with the plug- and play-style connections, you'll see just how easy we've made it to install.









Pickup Truck

Utility Vehicle

Tow-Behind

Flatbed Truck

| | | 1-PUMP ROADPAK (5 GPM) 450 lb Bead Tank Part # 25M701 | 2-PUMP ROADPAK (5 GPM) 450 lb Bead Tank Part # 25M703 | 2-PUMP ROADPAK (5 GPM) 1350 lb Bead Tank Part # 25M704 | 2-PUMP ROADPAK (10 GPM) 1350 lb Bead Tank Part # 25M706 | SLIDE-IN MOUNTING FRAME Part#24G627 | TRAILER TOW-BEHIND SYSTEM Part # 24M200 | 1-PUMP 2-GUN ROADPAK GUN ARM Part # 25M708 | 2-PUMP 2-GUN ROADPAK GUN ARM Part#25M709 | 2-PUMP 3-GUN ROADPAK HD GUN ARM Part# 25M710 |
|--------------------------------------|---------------------------------|--|--|---|--|--|--|--|--|---|
| | RPS Option 1 Part # 25D268 | • | | | | • | | • | | |
| | RPS Option 2 Part # 25D269 | • | | | | • | | • | | |
| EMS | RPS Option 3 Part # 25D270 | • | | | | • | | • | | |
| YST | RPS Option 4 Part # 25D271 | • | | | | • | | • | | |
| S L | RPS Option 5 Part # 25D272 | | • | | | • | | | • | |
| ROADPAK TRUCK-MOUNT SYSTEMS | RPS Option 6 Part # 25D273 | | • | | | • | | | • | |
| nck | RPS Option 7 Part # 25D274 | | • | | | • | | | • | |
| K TR | RPS Option 8 Part # 25D275 | | • | | | • | | | • | |
| DPA | RPS Option 9 Part # 25D276 | | | • | | • | | | • | |
| ROA | RPS Option 10 Part # 25D277 | | | • | | • | | | • | |
| | RPS Option 11 Part # 25D278 | | | • | | • | | | • | |
| | RPS Option 12 Part # 25D279 | | | • | | • | | | • | |
| | RPS Option T1 Part # 25M836 | • | | | | | • | • | | |
| ROADPAK TOW-BEHIND SYSTEMS | RPS Option T2 Part # 25M837 | | • | | | | • | | • | |
| ROAL DW-B SYST | RPS Option T3 Part # 25M838 | • | | | | | • | • | | |
| | RPS Option T4 Part # 25M839 | | • | | | | • | | • | |
| o F | RPS Option HD1 Part # 25D280 | | | | • | • | | | | • |
| AK H MOU EMS | RPS Option HD2 Part # 25D281 | | | | • | • | | | | • |
| ROADPAK HD TRUCK-MOUNT SYSTEMS | RPS Option HD3 Part # 25D282 | | | | • | • | | | | • |
| RC TRI | RPS Option HD4 Part # 25D283 | | | | • | • | | | | • |



| ROADPAK ADVANCED CONTROLLER Part # 25M711 | ROADPAK HD CAMERA SYSTEM Part # 24G634 | SIMPLE GUIDE SYSTEM Part # 24G634 | GUN LIFT WINCH KIT Part # 25M713 | REAR SEAT KIT Part # 25M716 | STEERABLE CARRIAGE Part # 24G634 |
|--|---|--|--|-----------------------------------|--|
| • | | • | | | |
| • | • | • | | | |
| • | | • | • | • | • |
| • | • | • | • | • | • |
| • | | • | | | |
| • | • | • | | | |
| • | | • | • | • | • |
| • | • | • | • | • | |
| • | | • | | | |
| • | | • | | • | |
| • | | • | • | • | • |
| • | | • | | | |
| • | | • | | | |
| • | | • | | | |
| • | • | • | | | |
| | | | | | |
| • | | • | • | | |
| | | | | | |
| • | | • | | • | |
| | | | | | |

CUSTOMIZE YOUR ROADPAK SYSTEM

Graco offers you a simple and fast way to order a custom RoadPak System to meet your striping needs — now and in the future. Design your own striping system by following the Easy-to-Design steps below.

CHOOSE YOUR ROADPAK SYSTEM

| PART # | DESCRIPTION |
|--------|---|
| 25M701 | 1-Pump, 5 GPM RoadPak System w/ 450 lb bead tank |
| 25M703 | 2-Pump, 5 GPM RoadPak System w/ 450 lb bead tank |
| 25M704 | 2-Pump, 5 GPM RoadPak System w/ 1350 lb bead tank |
| 25M706 | 2-Pump, 10 GPM RoadPak HD System w/ 1350 lb bead tank |

CHOOSE YOUR GUN ARM MOUNTING SYSTEM

| PART # | DESCRIPTION |
|--------|---------------------------------------|
| 24G626 | Single Hitch Mounting Frame |
| 24G627 | Slide-In Mounting Frame |
| 24M200 | Tow-Behind Trailer Kit Complete |
| | (not to be used with 1350 lb bead tan |

CHOOSE YOUR GUN ARM PART # DESCRIPTION

| 25M708 | 1-Pump, 2-Gun RoadPak Gun Arm |
|--------|---|
| 25M709 | 2-Pump, 2-Gun RoadPak Gun Arm |
| 25M710 | 2-Pump, 3-Gun RoadPak HD Gun Arm |
| | (includes 2nd wheel and longer gun mount bar) |
| 25D642 | RoadPak Additional Gun Kit |

CHOOSE YOUR CONTROL SYSTEMS

| DESCRIPTION |
|-----------------------------|
| RoadPak Advanced Controller |
| Rear Seat Kit |
| Steerable Carriage Kit |
| Gun Lift/Winch Kit |
| |

CHOOSE YOUR ALIGNMENT SYSTEMS

| FARI# | DESCRIPTION |
|---------------|--|
| 24G633 | RoadView HD Camera System |
| 24G771 | 6 mm HD Camera Kit |
| 24H555 | 16 mm HD Camera Kit |
| 24H612 | RoadPak HD Monitor Kit |
| 24G634 | Single Guide System |
| 241880 | Articulating Pointer |
| 17U930 | LazerGuide 3000 Long-Line Laser for RoadLazer |
| CHOOSE | YOUR FLUID MANAGEMENT ACCESSORIES |
| PART# | DESCRIPTION |
| 24G766 | RPS 2900 Complete Pump Kit |
| 24G769 | 33 Gallon (125 Liter) Paint/Water Tank |
| 24J149 | Bottom Feed Fittings Kit (for Paint Tank) |
| | Dottom i coa i ittingo itt (ioi i allit ialit) |

| 240140 | Bottom reed rittings for (for raint raint) |
|--------|---|
| 24H585 | RoadPak Accessory Frame Kit |
| | (for use with two 450 lb bead tanks or two 33 gallon paint/wate |
| | tanks or one of each) |
| 24G778 | RoadPak Stencil Gun Kit |
| 239934 | Paint Transfer Kit |
| 239935 | Paint Drum Agitator Kit |
| 24G774 | RoadPak Y-Strainer Kit |
| 24G777 | Solvent Siphon Kit |
| 24M142 | Solvent Siphon Kit (Tow-Behind only) |

| 25D643 | Pressure Balance Kit |
|-----------------|--|
| CHOOSE Y | OUR BEAD MANAGEMENT ACCESSORIES |
| PART # | DESCRIPTION |
| 24G765 | RoadPak 450 lb Bead Tank |
| 24H585 | RoadPak Accessory Frame Kit |
| | (for use with two 450 lb bead tanks or two 33 gallon paint/water |
| | tanks or one of each) |
| 25D608 | RoadPak 1350 lb Bead Tank with Frame |
| 24G775 | RoadPak Double Drop Kit |
| 238957 | Hand Bead Gun Kit |
| | CHOOSE Y PART # 24G765 24H585 25D608 24G775 |

RoadLazer RoadPak Tow-Behind System



Features & Benefits:

Bead Tank

450 lb (204 kg) bead capacity.

1 or 2-Pump

 Flexibility for those needing only 1-color or striping contractors who are growing into 2-color applications where it's easy to switch between yellow and white stripes with a twist of a lever.

RPS 2900 Hydraulic Motor

 No-stall design provides the reliability you can only get from Graco.

Endurance™ Piston Pump System

 Graco pumps have delivered excellent results in pumping striping paint for over 20 years.

Adjustable Gun Arm Beam

 Gun arm beam is located closer to the rear vehicle axle, assuring a more normal striping flow.

Double Acting Guns

 Air-assisted paint and bead guns offer excellent starts and stops.

Adjustable Bead Deflector

 The finger-adjustable bead deflector allows you to set the bead pattern to the exact width needed for the job (optional).

Dual Hitch System

 Patented design makes the hitches part of the striping vehicle, tracking with the truck, not behind it, delivering straighter lines and smooth transitions into curves.

Dual Wheels

• Four wheels create a smoother ride and protection from flats.

Video Guidance System

 Provides forward viewing for checking alignment while restriping or following control marks.

GrindLazer Standard Series

Typical Applications: Traffic Paint Removal, Thermoplastic Removal, and Smoothing Uneven Surfaces



| C: all | | Standard | DC07C |
|---------|------|----------|----------|
| (arınaı | 27Pr | Stannarn | 111.8/13 |

GrindLazer Standard DC89 G

| STANDARD SERIES | DC87 G | DC89 G |
|-------------------|-------------------------|-------------------------|
| Part Number | 25M842 | 25M843 |
| Cutter Type | Drum | Drum |
| Max Working Width | 20 cm (8 in) | 20 cm (8 in) |
| Drum Diameter | 12.5 cm (5.75 in) | 12.5 cm (5.75 in) |
| Drum Shafts | 4 | 4 |
| Engine/Motor | Honda 200 (6.5 HP) | Honda 270 (9 HP) |
| Engine Start | Pull Start | Pull Start |
| Air Filter | Cyclone | Cyclone |
| Tach/Hour Meter | Yes | Yes |
| Max Cut Rate | 30 m²/hr (300 sq ft/hr) | 40 m²/hr (400 sq ft/hr) |
| Vacuum Port | Yes | Yes |



GRACO Genuine Parts & Authorized Service

GrindLazer Professional Series

Typical Applications: Traffic Paint Removal, Thermoplastic Removal, Smoothing Uneven Surfaces, and Epoxy Removal



GrindLazer Pro DC1013 G

GrindLazer Pro RC813 G

GrindLazer Pro RC813 G DCS

| PRO SERIES | DC1013 G | RC813 G | RC813 G DCS |
|----------------------|-------------------------|--------------------------------------|----------------------------|
| Part Number | 25M846 | 25M847 | 25N669 |
| Cutter Type | Drum | Rotary | Rotary |
| Max Working Width | 25 cm (10 in) | 20 cm (8 in) | 20 cm (8 in) |
| Drum Diameter | 17.5 cm (7.75 in) | N/A | N/A |
| Drum Shafts | 6 | N/A | N/A |
| Engine/Motor | Honda 390 (13 HP) | Honda 390 Vertical (13 HP) | Honda 390 Vertical (13 HP) |
| Engine Start | Pull Start | Electric Start | Electric Start |
| Air Filter | Cyclone | Standard | Standard |
| Tach/Hour Meter | Yes | Yes | Yes |
| Max Cut Rate | 55 m²/hr (600 sq ft/hr) | 75 m ² /hr (800 sq ft/hr) | 75 m²/hr (800 sq ft/hr) |
| Vacuum Port | Yes | Yes | Yes |
| Depth Control System | No | No | Yes |



GrindLazer High Production Series

Typical Applications: Traffic Paint Removal, Thermoplastic Removal, Smoothing Uneven Surfaces, Epoxy Removal, and Inlay Grooving



GrindLazer HP DC1013 G

| HIGH PRODUCTION | DC89 G | DC1013 G | DC1013 G DCS |
|----------------------------|---------------------------|---------------------------|---------------------------|
| Part Number | 25M992 | 25M993 | 25N658 |
| Cutter Type | Drum | Drum | Drum |
| Max Working Width | 20 cm (8 in) | 25 cm (10 in) | 25 cm (10 in) |
| Drum Diameter | 17.5 cm (7.25 in) | 17.5 cm (7.25 in) | 17.5 cm (7.25 in) |
| Drum Shafts | 6 | 6 | 6 |
| Engine | Honda 270 (9 HP) | Honda 390 (13 HP) | Honda 390 (13 HP) |
| Engine Start | ProStart | ProStart | Electric Start |
| Air Filter | Cyclone | Cyclone | Cyclone |
| Tach/Hour Meter | Yes | Yes | Yes |
| Max Cut Rate | 55 m²/hr (600 sq ft/hr) | 75 m²/hr (800 sq ft/hr) | 75 m²/hr (800 sq ft/hr) |
| LineDriver Compatible | Optional | Optional | Optional |
| Max Cut Rate w/ LineDriver | 120 m²/hr (1300 sq ft/hr) | 160 m²/hr (1700 sq ft/hr) | 160 m²/hr (1700 sq ft/hr) |
| Vacuum Port | Yes | Yes | Yes |
| Depth Control System | No | No | Yes |



GRACO Genuine Parts & Authorized Service

GrindLazer High Production Series



GrindLazer HP DC1021 G



GrindLazer HP DC1021 G DCS

| HIGH PRODUCTION | DC1021 G | DC1021 G DCS |
|----------------------------|---------------------------|---------------------------|
| Part Number | 25M994 | 25N659 |
| Cutter Type | Drum, Reverse Cut | Drum, Reverse Cut |
| Max Working Width | 25 cm (10 in) | 25 cm (10 in) |
| Drum Diameter | 17.5 cm (7.25 in) | 17.5 cm (7.25 in) |
| Drum Shafts | 6 | 6 |
| Engine | Vanguard 630 (21 HP) | Vanguard 630 (21 HP) |
| Engine Start | Electric Start | Electric Start |
| Air Filter | Donaldson Heavy-Duty | Donaldson Heavy-Duty |
| Tach/Hour Meter | Yes | Yes |
| Max Cut Rate | N/A | N/A |
| LineDriver Compatible | Required | Required |
| Max Cut Rate w/ LineDriver | 195 m²/hr (2100 sq ft/hr) | 195 m²/hr (2100 sq ft/hr) |
| Vacuum Port | Yes | Yes |
| Depth Control System | No | Yes |






Stencils

- Alphabet & Number Sets
- Bike Lane & Pedestrian
- D.O.T. & MUTCD Highway
- FAA Airport & Heliport
- Handicap Parking Symbols
- Parking Lot Stencils
- Playground & Recreation



Highway Glass Beads Type 1

Embedding glass beads into highway safety markings creates reflective lines that shine though darkness, rain and fog to direct drivers more safely along the road.





Traffic Marking Paint

- **1** IDENTIFY THE DIFFERENT RESIN SYSTEMS
 - Water-base: Available in regular and fast dry resin systems. Provides ease of clean-up with water. Ideal for striping newly placed asphalt or sealcoat.
 - Solvent-base: Heavier-duty paints that provide better performance over concrete and when restriping existing lines. Ideal for crosswalks, curbs, warehouse aisles, re-striping, and other concrete substrates.
- **2** CHOOSE THE APPLICATION

| Sealcoat (freshly applied) | |
|----------------------------|--|
| Asphalt (new) | |
| Asphalt (old) | |
| Concrete | |
| Brick / Masonry | |
| Curbs / Medians | |
| Crosswalks / Stop Bars | |
| Parking Lot Stalls | |
| Airport Runways | |
| Warehouse Aisles | |
| Re-Striping Existing Lines | |
| | |



| | | | | | | | _,_ |
|----------------------------|-----------|---------|-----------------|---|----------|-------------|-----|
| / | LATEX | | THE HILBUILD F. | DRY LATEX | YLIC | RUBBER | |
| O O O O O O O O O REGULAD. | FAST DRY. | 4ST DOV | BUILD F. | O C O O O O O O O ACETONE | HLORINA. | ALKYD ALKYD | |
| • | • | • | # • | ••• | 0 | | / |
| • | • | • • • | • | • | • | • | |
| • | 000 | 0 0 | • | 0 | | | |
| • | 0 | • • | • | 0 | 0 0 | 000 | |
| 0 | | | | | | | |







PreMark® Manhole Protection Rings

- Subtle incline that provides smooth, damage-free ride for daily traffic
- Each ring is made of durable non-beaded 125 mil Preformed Thermoplastic
- As many as three Preformed Thermoplastic rings can be combined to negotiate severe grad changes
- · Requires no minimum air or road temperature





PreMark® Pavement Markings









- Lasts 6 to 8 times longer than paint with a clean, crisp appearance
- No "alligator" cracking that can occur with hot-applied thermoplastic
- · Impervious to oil and gasoline
- Made with up to 60% recycled material
- 24-month shelf life
- No surface preheating required, allowing for year-round application
- · Precut and ready to use
- · No specialty equipment or expensive custom tools needed
- · ADA-compliant pedestrian and wheelchair friendly surface
- Facility is ISO 9001:2015 certified for the design, development and manufacturing of preformed thermoplastic


Ennis Flint 3000 EX Heat Torch



- This UL-listed heat torch features an electric ignition, hand guard, deadman trigger and an automatic POL valve for maximum safety.
- Spare igniter stored in the trigger guard compartment.
- Designed for applying performed thermoplastic pavement markings and adhesives.
- · Gel-coated comfort grip.

Custom Logos and Horizontal Surface Signage





- Lasts 6 to 8 times longer than paint with a clean, crisp appearance
- · 33 standard colors
- ADA compliant Pedestrian and wheelchair friendly surface
- · Fast installation and minimal traffic downtime
- · Precut, interconnected shapes and colors; easy to handle
- Facility is ISO 9001:2015 certified for the design, development and manufacturing of preformed thermoplastic
- · No specialty equipment, custom tools, templates or grids needed







Decorative Crosswalks and Traffic Calming Surfaces



- Designed to improve traffic safety at intersections and multi-use paths
- Interconnected, 125-mil sheets with anti-skid elements
- · As material wears, new anti-skid elements are exposed
- · Available in a variety of patterns, borders and colors
- Less work and maintenance than traditional pavers
- · No custom tools, templates or grids needed
- Open to traffic within minutes of application
- · ADA-compliant pedestrian and wheelchair friendly surface
- Facility is ISO 9001:2015 certified for the design, development and manufacturing of preformed thermoplastic










Survey Marker Flags

Wire, Plastic and Fiberglass Staff Flags

With 1,000 flags per box we will have you covered with plenty of flags to suit your needs. You can even mix and match colors and have them customized with your logo.

Choose your size, style and color!





Caution Barricade Tape

Roll Flagging

Ink Color Roll Flagging 12 rolls per box

white / red

white / yellow

<u>Patterns Available:</u> stripes, polka dots, and checkerboards. Size 1/3/16" wide <u>Ink Colors Available:</u>

| white / black | black / blue | black / yellow | yellow |
|------------------|--------------------|----------------|--------|
| white / blue | black / blue glo | yellow red | black |
| white / green | black / green | green | orange |
| white / orange | black / orange | red | white |
| white / pink glo | black / orange glo | blue | |

black / pink glo

black / red








Preformed Thermoplastic

AirMark® is a durable preformed thermoplastic pavement marking material. Whether the need is for linear delineation or horizontal surface signage, AirMark® is best suited for markings such as taxiway, hold position, geographic position, vehicle roadway, aprons, ramps, and at aircraft parking and tie downs.

Sherwin Industries, Inc. is a Certified AirMark Applicator

BENEFITS OF USING AIRMARK®

- Application only by AirMark® Certified Applicators using large infrared heater according to specification
- Designed for use on taxiways, ramps, aprons, gates, as well as vehicular roadways on the airside
- Application method has significant advantages, especially in application of multi-color markings that are typically labor intensive using paint
- Retroreflective glass beads are mixed throughout material at time of manufacturing. As the marking wears new beads are exposed for retained retro reflectivity
- · Long lasting color pigments are organic and contain no heavy metals
- · Resistant to aviation fuels, motor fuels, lubricants and de-icers
- Facility is ISO 9001:2015 certified for the design, development and manufacturing of preformed thermoplastic
- Inscriptions on surface signage made according to current FAA AC 150/5349-1 or ICAO standards accordingly









Standard Colors













Phone: 800-525-8876 • Fax: 414-281-6404

Lighted Runway Closure Marker



- · Fitted with LED Bulbs for long life
- · Easily set up by one person in 2 minutes
- · Lighted "X", when opened, spans 20'6"
- · Warning light for failure indication
- Full fuel load (20 gal.) capacity of over 200 hours
- Raised and lowered by Electro Hydraulic Assist

Features

- 2" trailer frame steel w/2000 lb. axle
- DOT approved lighting technology
- Four (4) 5,000 lb. jack stands for support
- Operated with On-Demand generator and DC power
- Auto dimming for nighttime operation
- · Optional heavy duty protective cover



OPTIONAL - S1703 (not included in Standard Specifications)

- Heavy-duty coated vinyl Lighted X covers
- Anti-mildew with UV pigments
- · Color yellow

Low Profile Barricade

- 8 ft. long and 10 in. high barricade, units interlock
- Durable construction, 25 lbs
 - enhanced wall thickness on barricade bottom
 - molded reinforcing ribs add stiffness and strength
- · Connectors are molded into the barricade, no pins to lose
 - allows interconnected units to pivot in multiple orientations between 90° and 180°
- · 7° angled sidewall
 - facilitates visibility
 - accepts 70"L x 6"H continuous retroreflective sheeting
- · Fill with up to 220 lbs. (26 gallons) of water
 - two fill holes and one drain hole
- · Accepts two styles of lights
 - 360° round, screw on airport lights
 - standard barricade, bolt on lights


· Two flag mounts

FAA Advisory Circular

No. FAA AC150/5370-2G

- · FOD (foreign object debris) Free
- · Forklift access, recessed areas at bottom of barricade
- Stackable for transportation and storage

 multiple stacking lugs keep units in place while stacked



Barricade Lights

S601





Features

- Utilizes 4 LEDs to project a 360 degree flashing light pattern
- · Lasts 76 hours after fully charged
- · Internal solar panels allow light to exit through top of dome giving more visibility to pilots
- Standard 2" water pipe thread allows for easy installation
- · Poly carbonate dome and base
- Manual external on/off switch

S562

Features

- Solar powered
- Ambient light sensing,
 - turns on automatically in low light
- · 4 LED bulbs
- Flashing
 - 55 Flashes per minute

630



Features

- · Meets and exceeds I.T.E. specs. for Type D
- Utilizes 4 LED bulbs to project an omni-directional light pattern.
- · Available in steady burn or flashing configurations.
- · Manual on/off switch



Phone: 800-525-8876 • Fax: 414-281-6404



Airport Safety Construction Flag (Follow Me)

Item # \$6040

Description 36" x 36"

60" Wooden Mast for Flags

Item # S6041



Safety Flag 20" x 20" with Diagonal, 30" Staff

Part Number Color SFKVP20-30 Orange SFKVP20-30W White



Airport Taxi-way & Runway Light Markers

Item # 1308105

Description 28" Threaded
End Markers. Sold in pairs.

Item # 1308110

Description 36" Threaded
End Markers. Sold in pairs.



Replacement Airport Windsocks

Our highly visible and durable windsocks are made of Fluorescent nylon fabric.

| Item # | Throat | Length |
|---------|--------|--------|
| ASX1036 | 10" | 36" |
| ASX1896 | 18" | 96" |
| ASX3612 | 36" | 144" |

(Other sizes available upon request)

Windsock Hardware

Manufactured from $\frac{1}{4}$ " cold rolled steel. A machined bearing is added that allows the windsock to respond to the slightest wind.

| Part # | Description |
|--------|--|
| BFX10 | 10" Windsock Machine Bearing Frame |
| BBX18 | 18" Windsock Double Ball Bearing Frame |
| BBX36 | 36" Windsock Double Ball Bearing Frame |

(Other sizes available upon request)

Bowmonk AFM2

SBOW009



FAA Approved for Winter Runway Friction Testing Standard Features

- 32 character high contrast alpha-numeric liquid crystal display with back lighting for night-time visibility.
- Tactile switches, with beep, for selection purposes
- · Automatic cancellation of faulty friction tests
- · Manual cancellation of any test if required
- Provides for temporary suspension of friction testing with no loss of recorded data
- Stores up to 99 friction readings
- · Compatible with ABS braking systems
- Permits field programmable airport name runway and operators through keypad or bar codes
- · No mounting kit or connections to vehicle are required
- 128k byte CMOS memory with battery backup
- · No connection to vehicle required
- Built in 6 volt rechargeable battery (external voltage for battery recharge 9v to 18v DC) powers unit for at least 12 hours. Can be recharged from main power pack or car cigarette lighter outlet

The FOD*Commander

FC2400-4MC



The FOD Commander is an innovative FOD sweeper that quickly and efficiently cleans up debris from the runway and ramp area. This lightweight and maneuverable unit allows for easy install and simple cleanup. This unique design uses friction to lift material from the ground, allowing airflow and the unit's forward motion to scoop and trap debris from fine sediment to large sticks and tools.

- Effective tow speed: 6MPH (10KPH) to 30MPH (50KPH)
- Sweeping Width: 8ft (2.43M)
- · Easy debris removal
- Single person operation
- 150/5210-24, 5.2b Non-Mechanical Systems
- · All weather operation








Vinyl X-It





Features

- 1) Lightweight 50 lbs. per piece
- 2) Porous
- 3) Vinyl coated polyester fabric
- 4) Inexpensive
- 5) Weighted ends
- 6) Swivel in middle
- 7) Custom sizes available

Benefits

- 1) Easy to install, move, pickup and store
- 2) Aesthetically pleasing yellow & orange
- 3) Lets rain & wind through
- 4) Tough & durable won't stretch, shrink or fade
- 5) Non-budget item
- 6) Pieces can be rolled together for ease of storage
- 7) Any situation or size can be accommodated

Standard Size 60' x 10' (2 pieces to make a full X-it). Standard Size 30' x 5' (2 pieces)

Hydraulic Digital Scale Indicator

Part # TR-1-NK-HE

- Water-resistant corrosion proof enclosure with stainless steel adjustable stand/mount
- Weigh while loading eliminates wasted time
- · Weight totalization feature.
- Lock-on-Weight for stable viewing and totaling of weight.
- · All pushbutton controls
- Data output for printer or computer
- Super bright LED display
- · Temperature compensated sensor supplied
- Optional label printer or thermal tape printer
- Optional On Board Printer
- · Optional Wireless Printer System
- · Use on Forklifts and Loaders
- Converts Hydraulic Pressure to Readable Weight Display



Airport Glass Beads Type III



Item #SGBTY3 (1.9 Index of Refraction (IOR)) airport beads has the best retro-reflectivity, initially and over time. Type 3 - TT-B-1325D (50lb bags)

Urethane and Rubber Cutting Edges

Urethane Advantages:

- · It reduces damage to in-ground lighting.
- It reduces impact on plows, blowers, and vehicles when solid edges, objects or surface changes are impacted.
- It greatly reduces driver fatigue.
- It reduces vibration.
- It will outlast rubber by approximately 8:1 in applications requiring low impact cutting edges.
- Urethane cutting edges are multi-adjustable for extended use.
- Blades are custom cast to customer requirements for thickness, length, width, edge angle, and mounting bolt patterns.
- Water and slush are squeegeed out of shallow depressions preventing ice spots from forming.



Rubber Advantages:

- Flexible
- Wear-resistant
- · Press cured, not extruded
- No gouging
- · Safe High-speed runs



FlexStake

FlexStake makes five markers that are particularly well suited for airport use. Because of their ability to withstand multiple traffic hits at up to 80 mph, the FlexStake HD, SM, and TM are used on runways and taxi strips. At speeds up to 80 mph, these posts can be run over by a plane without damage to landing gear or post.





Phone: 800-525-8876 • Fax: 414-281-6404

ANSI Class 3 Outerwear



LUX-ETJBJ Value Bomber Jacket M to 5XL



LUX-TJBJ-B 4-Way Original Bomber M to 6XL



LUX-TJBJ 4-Way Original Bomber M to 6XL

S-5XL



Other options available upon request

ANSI Class 3 Sweatshirts



LUX-SWT3HZ Sweatshirt S-5XL



LUX-SWTHZBK LUX-HZSWTBX (B-Back CSA Z96-15) Sweatshirt • S-5XL

LUX-CSWT Sweatshirt S-5XL

ANSI Class 2 Sweatshirts



LUX-SWTLH
Light-weight
Hooded
Sweatshirt
S-5XL



LUX-SWTLHZ
Hoodie
with zipper
S-5XL





ANSI Class 3
Vests



ANSI Class 2 Vests





ECO-ATRNSMX-Lime ECO-ATRNSMX-Orange S to 5XL

Other options available upon request

ANSI Class 3 T-shirts



LUX-SSETP3B
Orange and Yellow
S-5XL
Tall Size: LT-6XT (Yellow only)



LUX-LSETP3B
Orange and Yellow
S-5XL
Tall Size: LT-6XT (Yellow only)



LUX-LSETPBK Orange and Yellow S-5XL

ANSI Class 2 T-shirts



LUX-LSET2B Orange and Yellow S-5XL



LUX-SSETP2B Orange and Yellow S-5XL



LUX-SSETPBK
Orange and Yellow
Black Bottom
S-5XL

Other options available upon request



Rain Gear

LUX-TJR Class 3 Rain Jacket

S to 5XL Orange or Yellow



LUX-TENR

Class E (when worn alone) Rain Pants S to 5XL

Protection Headwear

REGULAR BRIM HAT

V100 SQUEEZE LOCK SUSPENSION **V200 RATCHET SUSPENSION**

· 6-point deluxe Nylon suspension

- Meets ANSI Z89.1 Type 1, Class E & G
- · Front Cotton terry sweatband
- Rain trough and accessory slots
- Hard hat shell Made in USA





















FULL BRIM HAT

VF200 RATCHET SUSPENSION

· 6-point deluxe Nylon suspension

· Meets ANSI Z89.1 Type 1, Class E & G

 Front Cotton terry sweatband

 Metric tables and °C/°F temp conversion graph printed under brim

Hard hat shell Made in USA

















ANSI Z89.1: Standard for performance and testing requirements

- impact, penetration and electrical insulation

TYPE I: Meets stringent vertical impact and penetration requirements

Class E (electrical): Tested to withstand 20,000 volts Class G (general): Helmets are tested at 2,200 volts

Footwear



87151 Plain Toe

Knee Boot

87251 Steel Toe

Knee Boot



SaniSpray HP

SaniSpray HP Sprayers provide the highest airless and ELECTROSTATIC spraying power. They deliver consistent coverage faster, using less labor, allowing businesses to operate safely.

Choose the Right Sprayers for Your Jobs









| SPRAYER | SaniSpray HP 20 Corded & Cordless Handheld Sprayer | SaniSpray HP 20 ELECTROSTATIC Cordless Handheld Sprayer | SaniSpray HP 65 Corded & Cordless Portable Hopper Sprayer | SaniSpray HP 130 2-Gun Cart Airless Sprayer | SaniSpray HP 750 4-8 Gun Cart Airless Sprayer |
|----------------------------|--|--|--|--|--|
| AIRLESS Technology | ✓ | √ | √ | √ | √ |
| ELECTROSTATIC TECHNOLOGY | | √ | | | |
| | LOW — Up to 15 Gallons Per Week | LOW — Up to 15 Gallons Per Week | MEDIUM — Up to 50 Gallons Per Week | HIGH — Up to 100 Gallons Per Week | HIGHEST — Up to 500 Gallons Per Week |
| PRODUCTION NEEDS | LOW — Up to .019 in Tip/ Up to 20 fl oz per min | LOW — Up to .019 in Tip/ Up to 20 fl oz per min | MEDIUM — Up to .023 in Tip/ Up to 65 fl oz per min | HIGH — Up to .031 in Tip/ Up to 130 fl oz per min | HIGHEST — Up to .031 in Tip/ Up to 750 fl oz per min |
| | 1 Gun | 1 Gun | 1 Gun | Up to 2 Guns | Up to 8 Guns |
| | _ | _ | Up to 300 ft of Hose per Gun | Up to 300 ft of Hose per Gun | Up to 500 ft of Hose per Gun |
| MATERIAL CAPACITY | 42 oz Flexliner™ (or) 3 Gallon ProPack | 42 oz Flexliner™ (or) 3 Gallon ProPack | 1.5 Gallon Hopper | Spray from Any Container | Spray from Any Container or from Included 10 gal hopper |
| POWER SOURCE | CORDED — 120V CORDLESS — 20V DeWALT® Lithium-Ion Battery | 20V DeWALT Lithium-Ion Battery | CORDED — 120V CORDLESS — 60V DeWALT FlexVolt® Lithium-Ion Battery | 120V Corded | 240V Corded or 120V Corded with optional accessory |
| MATERIAL Compatibility* | CORDED — List-N Disinfectant Materials that are Non Alcohol- Based (Non-Flammable) CORDLESS — All List-N Disinfectant Materials | List-N Disinfectant Materials that are Non Alcohol-Based (Non- Flammable) | All List-N Disinfectant Materials | All List-N Disinfectant Materials | All List-N Disinfectant Materials |
| JOB SIZE | Any Small Jobs — Tables, Door Handles, Cars, Desks, etc | Any Small Jobs — Tables, Door Handles, Cars, Desks, etc | Any Small to Mid-Sized Jobs — Restaurants, Schools, Hotels, etc | Any Mid to Large-Sized Jobs — Bus Fleets, Dealerships, Arenas, Hotels, Schools, etc | Any Large-Sized Jobs — Sport Venues, Amusement Parks, Zoos, etc |

RAC-Plus-I

RAC-Geo-II

...the standard in distance measuring instruments





The RAC-Plus-I brings the accuracy, reliability and productivity of using a vehicle installed distance measuring instrument within the reach of everyone.

All distance and speed information can be read directly from the RAC-Plus-I's display — no software is required to view your data.

The RAC-Geo-II includes all the benefits of the industry standard RAC-Plus-I while also allowing you to save your distances, coordinates and customized ID markers in the unit's expansive memory.

Accurate up to 1 foot per mile.

Download data into the RACPro Software to quickly generate reports, graphs, maps, spreadsheets and more. The RAC-GEO-II real-time data collection option even lets you measure and collect data in real time!

ROADWATCH Pavement Temperature Sensor



The Roadwatch system provides vehicle operators crucial surface temperatures. Whether you need the temperature to know when to adjust the type and amount of 'salt' spreading, drive more cautiously, or use the information to determine if temperatures will allow paint to adhere properly.



- · Unmatched reliability
- · Fully-sealed sensor
- · Connector mating inside sleeve
- · No screws or openings in sensor face
- · Environmentally tested

| Part Number | Description |
|--------------|--|
| 849-1262-002 | Roadwatch® System Kit °C (sensor, display, cable, and mounting hardware) |
| 849-1262-003 | Roadwatch® System Kit °F (sensor, display, cable, and mounting hardware) |
| 849-1243-001 | Roadwatch® Sensor with mounting hardware only °C |
| 849-1243-000 | Roadwatch® Sensor with mounting hardware only °F |

The Bowmonk BrakeCheck Portable Brake Tester

The Bowmonk BrakeCheck is a fully self-contained, user friendly, portable brake tester, used by workshops, government traffic authorities and Authorized Test Facilities (ATF's) around the world.





- Portable
- DVSA-approved
- · For all Vehicle Classes
- · Tests Service and Hand Brake
- Suitable for ABS-equipped Vehicles
- Portable Printer Available
- Download Data to PC

Part Number

SBOW804

SBOW123

- Motorcycle Mounting Bracket Available
- Multiple Variants for Different Vehicle Types

SAMPLE OF PRINT OUT

BrakeCheck

Serial No: BRK00176 S/W Version: 1.0.05

Test Performed:

12:17:45 03/06/2003

Service Brake Test

==============

Front-Back Deceleration Peak: 90%g Average: 65%g

Left-Right Acceleration

Peak: 5%g Vehicle Pulls: Right Test Speed: 35 km/h

Stopping Dist: 7.5m

Brake Efficiency: 64%

Calibration Ok

Due: 06/06/2005

Vehicle Registration

•••••

Inspector Name

Signature

SBOW-KIT Bowmonk BrakeCheck System with standard accessories: Includes: BrakeCheck with battery charger Carrying Case · Infrared printer · Case of Replacement Paper 10 rolls per case **SBOW801** BrakeCheck with battery charger **SBOW813** BrakeCheck carrying case **SBOW808** Infrared Printer **SBOW026** Case of Replacement paper 10 rolls per case **Optional Accessories**

PC Download Cable

Cab Check PC Program

Description



Bowmonk SensorCheck

The ABS/EBS Sensor & Exciter Ring Diagnostic Tool

Lightweight and portable, the SensorCheck comes supplied with two 1.6m high quality cables, short introductory printed manual, and a single 9V battery — everything, in fact, needed to use it straight out of the box.

Test for the six most common causes of EBS/ABS faults on trucks, trailers and buses in just 15 seconds:

- · Correct Ohms resistance
- Open circuit
- · Short circuit
- · Pole ring tooth damage
- · Pole ring misalignment
- · Sensor gap measurement

Item #SBOW830



Bowmonk 2000-R



Bowmonk Electronic Brake Meters are the most up to date and versatile instruments available for brake and skid testing, road traffic accident investigation and reconstruction and vehicle safety inspections.

- Portable
- DVSA-approved
- Supports Pedal Force Transducer
- · Built-in Printer & Keyboard
- · Also measures Acceleration
- · Easy to Use
- For all Vehicle Classes
- Tests Service and Hand Brake
- Download Data to PC
- Built-in GPS for recording test location and synchronising time
- · Results are stored as csv files (no special software required)
- · Lithium Ion battery gives more test cycles per charge

Part # SBOW200-R Bowmonk 2000 Brake Meter
Part # SBOW111-R Pedal Force Transducer

Part# SBOW814 Battery Charger / PC Download Cable



MUTCD Signs

Sherwin Industries, Inc. offers a wide variety of signs, reflective sheeting, posts, mounting, brackets and strapping accessories.



- Regulatory Signs
- · Handicap Signs
- Toll Road Signs
- · School, Playground Signs
- Warning Signs
- Workzone Signs
- · Guide-Conventional Road Signs
- Guide-Freeway & Express Way Signs
- Street Signs
- Custom Signs



Overlays

All overlay panels attach to sign faces with durable, weather resistant brass snap button fasteners. Velcro may be used upon request. Signs and overlays are designed so that overlays may be attached to the back of the sign for storage.



Standard and Custom Roll-Up

For daytime use we offer **Premium Mesh** and **Non-Reflective Vinyl** with superior fade resistant UV stabilizer. For daytime as well as nighttime usage, we offer **Standard Reflective** and **High Performance Reflective** materials.



Roll Up Sign Sheeting

Diamond Grade™ (DG)

3M™ Diamond Grade™ Roll-Up Sign Sheeting Series RS20/RS24 is a visible light-activated fluorescent wide angle prismatic lens reflective sheeting designed for the production of Roll-Up traffic control signs used in construction work zones. This sign sheeting is designed to provide higher nighttime sign brightness than sheetings that use glass bead lenses. RS24 sheeting has higher daytime brightness than ordinary (non-fluorescent) colored sheeting. Series RS20/RS24 sheeting is backed with a strong, flexible, gray-coated fabric.

| <u>Color</u> | Product Code |
|--------------|--------------|
| White | RS20 |
| Fluorescent | |
| Orange | RS24 |



High-Intensity

3M™ Roll-Up Hi-Intensity Sign Sheeting Series RS30 consists of retroreflective microprisms formed on a flexible glossy and UV-stabilized polymeric film, designed for the production of roll up traffic control signs used in work zones and emergency traffic control. This sign sheeting is designed to provide higher nighttime sign brightness. Series RS30 sheeting has a protective film on the facing side and is backed with a heavy duty vinyl coated fabric.

| Color | Product Code |
|-------------------------------------|---------------------|
| White | RS30 |
| | RS34 |
| Fluorescent Pink Fluorescent Orange | RS33 |

Non-Reflective Fluorescent Orange Roll-Up Signs

Non-Reflective Fluorescent Orange Roll-Up Signs are constructed of a fabric reinforced UV stable vinyl. This construction will not delaminate and provides excellent durability and fluorescence stability.

Non-Reflective Fluorescent Orange Roll-Up Signs are suitable for maintenance and moving operations. They are intended for daytime use only. They are not intended for use during night operations or low light conditions.

Marathon (M)

Reflexite's Roll-Up sign blanks which utilize Marathon Fluorescence take performance to a higher level. The longer lasting fluorescent color gives the sign a longer useful life and offers outstanding visibility, day and night. Higher levels of photometric performance ensure superior reflectivity at night and in low light conditions. Reflexite high Performance Marathon Fluorescence signs are available in the following colors: fluorescent orange, fluorescent yellow-green (lime), non-fluorescent white, and the new fluorescent yellow.

Color

Marathon Fluorescent Orange Fluorescent Yellow-Green (lime) White Fluorescent Yellow



Roll Up Sign Sheeting

Super Bright (SB)

This is one of Reflexite's most popular products. Super Bright fluorescent prismatic sign blanks are used by our customers to create the work zone signs you see on the road. As a motorist, you benefit from maximum visibility at long distances, day and night. Reflexite's color stability technology ensures a long and useful life. Super Bright colors are: fluorescent orange, non-fluorescent white, yellow and the new fluorescent pink color recommended for Incident Management applications.

Color

Fluorescent Orange White

Fluorescent Pink Yellow

Premium Mesh

Bone Safety Signs' true fluorescent orange mesh is flexible, breathable, and mildew resistant. Great strength and durability, along with high color visibility, make this fabric ideal in safety applications.

Color

White

Fluorescent Orange

Sign Stands

Sign Stands come with our patented Auto-Latch mechanism, unless our Universal Bracket is requested. The advantage of our Auto-Latch is the speed in which the sign is attached and released from our stands.

- · Crash Design Breakaway Base
- Exclusive Quick Release System for all modular attachments and accessories
- · Compact and Lightweight
- Bright Orange, UV Stabilized, Powder Coated Legs, for Safety, Durability & Visibility
- Pull Pin and Kick Release for fast setup by hand or foot
 Simple Nut & Bolt Construction allows for fast repairs using basic hand tools
- Readily available Replacement Parts or Assemblies
- 3 Height Adjustments on Legs for Use on Uneven Terrain




Pedestrian Crossing Product Line

The Green Cross system is most effective on unsignalized low-speed two-lane streets. The mobility of the Green Cross system allows it to be taken in and out of the street during the school day, enhancing the effectiveness of the system.

- Durable yet extremely lightweight safety posts to highlight crosswalk areas
- Fixed and Portable bases, all designed to withstand the rigors of vehicle impacts
- Highly reflective crosswalk flags and STOP paddles
- NCHRP 350 accepted
- The fluorescent yellow-green colors create great day and night visibility
- Multiple options of reflective signs to meet local requirements.











Impact Recovery Signs

And why the IRS System is the best on the market!

The heart of the system is a unique reactive spring with the strength to support not only a flexible post, but an information panel as well. This reactive unit gives upon impact and is designed to reorient the panel towards traffic. The introduction of the new "Anti-Twist Feature" assures the sign will return to its' original position after impact.





"Anti-Twist Feature"





Type I and Type II Barricades

Traffic control devices help to insure roadway safety by providing direction for orderly and predictable movement of all traffic. They also help in the protection of construction crews and motorists on streets

and highways.

Meets MUTCD Standards



Combocade Barricade Steel legs Plastic boards



Plasticade Barricade
One piece construction
Ballast Internally



Econocade Barricade
One piece
Solid construction



Nood Barricades

Fibercade Barricade Modular components

T3B™ Barricade

Meets MUTCD Standards



Telespar & Angle Iron feet available



Upright snaps into the base



All plastic and collapsible

A-Frame Barricades

A-Frame is made from a durable, yet lightweight plastic that will not rot, rust, crack or peel. The double slotted frame will hold either one or two panels. Various reflective sheeting grades available.



O-Frame Barricades

Parade Style "A-Frame" Barricade

Instantly create an MUTCD-compliant Type I or II barricade.

O-Frame impact-resistant and UV-stable thermoplastic barricades are designed for low-speed municipal applications including crowd control, parking control and plank box utility closures. They are ideal for cordoning off an area during public events.

- Accommodates 1" or 2" plastic or wood panels
- Panels available in 4, 6, 8, 10 and 12-foot standard lengths
- Panels and legs available for purchase separately or together
- Legs stack for easy storage
- · Choose Engineer, High Intensity or Prismatic sheeting

LED and Solar Barricade Lights

Consists of Type A/C, D Cell, 6-Volt standard and B-lights, Solar lights, 360 degree lights, Barge lights and contractor (sale) lights. You can tailor your light by using different housing colors and/or lens colors.

All lights come packaged with bolts, wrenches and pins.



Crowdcade Crowd Control Barricade Systems



6' long, durable plastic barricade with strong plastic legs and rubber feet



Deluxe 7' long, thick walled, plastic barricade with steel legs and feet

Work Zone Safety





Stop/Slow Paddles

 Paddles are available in hand held or staff mounted versions.



Traffic Drum

- Meets MUTCD specifications
 18" minimum diameter
- Two piece break-away construction
- · Built in anti-roll design
- Able to display one or two type "A" or "C" lights
- Available with or without reflective sheeting
- Large built-in handle
- NCHRP-350 Crash Worthiness

Work Zone Safety





Spring Cone™

- · Compact for easy storage
- Meets MUTCD requirements for 28" highway traffic cone
- Flexible Spring Cone[™] spills wind for increased stability
- Cone is made of a durable, bright orange, flexible mesh material



Traffic Cones

- · Injection molded design
- Maintains color in difficult UV situations
- Black bases are made entirely from recycled materials
- · Multiple heights available



Colored Cones

- Available in lime green, dark green, yellow, red, white, sky blue, navy blue and pink
- 18" and 28"
- With or without collars
- MUTCD and NCHRP-350 compliant



Cone Bar

| Technical Specifications | |
|--------------------------|---|
| Length | 3.0 ft' adjust to 6.0 ft' 6.0 ft' adjust to 10.0 ft' |
| Material | ABS |
| Weights | 1.35 lbs |
| Cone-Bar ring diameter | 0.28' |



Pack and Pop Collapsible Cone

- Internal light has two settings: steady burn and flashing
- Cone light endures 100,000 flashes or 36 hours of steady burn
- · Operates on 2 'AAA' batteries (included)
- 18" and 28" Pack and Pop Cones have 1 L.E.D. internal cone light-bulb and 30" Pack and Pop Cones have 4 L.E.D. internal cone light-bulbs

Work Zone Safety


Gemstone™ Vertical Panel

- Oversized handle with comfort grip can be picked up easily, even with light attached
- · Designed to withstand repeated impacts and minimize damage to vehicles
- · Recessed panel protects sheeting — 8"W x 36"H
- Gemstone side wall provides strength & durability
- · Flashing light mounting receptacle



GAI





- Two sizes
- 42" (47" with handle), 1.7 lbs.
- 28" (33.6" with handle), 1.25 lbs.
- · Recessed areas accept two bands of sheeting protects retroreflective sheeting from rips and scratches
- · Flange on bottom grabs base for tight fit
- Recycled rubber bases, 8, 10, 12, and 18 lbs
- MASH Accepted, Meets MUTCD Standards

Open Top Delineators

- Two sizes, 42" and 28"
- Post diameter 5.375"
- · Flange on bottom grabs base for tight fit, 6" dia.
- Quick to set up
- · Reflective bands, 3" or 4" wide
- · Durable polyethylene
- · Recycled rubber bases, 8, 10, 12, and 18 lbs.
- Weight: 42"H 1.7 lbs., 28"H — 1.1 lbs.
- NCHRP-350/MASH Accepted. Meets MUTCD Standards









Navicade™ 28



Light can only be used on 42" Navicade

Navicade™ & Navicade™ 28

- 42" (50" with handle) and 28" (35.5" with handle) channelizers
- Slim design perfect for narrow roadways where space is an issue
- Very durable, designed to rebound after impact
- Oversized handle easy to grab with gloved hand or light attached.
- Stackable with or without base for easy transport and storage
- 42" available with 4 bands of sheeting choose 6" and/or 4" bands
- 28" available with 2 bands of sheeting choose 6" and/or 4" bands
- Solid recycled rubber bases in three weights 10 lbs., 16 lbs, and 30 lbs.
- Stenciling available
- Navicade 42" is MASH Accepted WZ-301, Meets MUTCD Standards
- Navicade 28 is MASH Accepted, Meets MUTCD Standards

LED Warning Lights



Micro-Burst

- · Two Flash Patterns to choose from
- LEDFL375-A, 60 Single Flash /Min
- LEDQ375-A, 72 Quad Flashes/Min (same light source)
- Magnet or Permanent Mount
- 12/24VDC and 120VAC versions available
- Sonic-Welded
- 5 Year Warranty



PSLM₂

- All-purpose multi-use signal light
- 300-400 hours on 2 "D" batteries (not included)
- · Magnet mount base included
- Optional photocell operation for night time use
- Available in: Amber, Red, Clear, Green or Blue

High Power LED Low Profile Mini Bars

MMBLEDLP

- 12/24V, 17.25", 2.75" tall
- · Aerodynamic 360 degree
- · 24 high power LED's
- Maximum current draw is 4.0 Amps
- · Dome: Amber, Red, Blue, Clear
- Additional LED colors: Clear, Red, Blue, Green





Dash Mount Switch SSWMS



Mag Mount Switch C&P2B

MINILP

- 12/24, 13.5", 2.75" tall
- Aerodynamic 360 degree
- 18 high power LED's
- Maximum current draw is 3.0 Amps
- · Dome: Amber or clear domes only



Economy Low Profile LED Micro Mini Bar

MMBZLEDFL

- 12/24, High impact LED display
- · Low current draw, 1.4A at 12.8 volts
- Magnet mount includes: 3-90lb pull magnets, 15' straight cord and plug with on/off switch
- 2.75" low profile dome, 17.25" wide
- · 3 unique flash patterns



High Power Low Profile LED Light Bar

MBX24-C/A

- 12/24, 10 amber LED modules
- · 3" tall housing
- · Current draw: 5A maximum
- 30 total high power LED's
- 23" x 8" deep x 4" tall with legs installed
- Magnet mount includes: 4-75lb pull magnets, 15' cord and plug with on/off and pattern changing switch built in
- · Available in Amber, Red, Blue, Green, White and Violet



Pavement Markers


RPMs and Halftracks

RPMs and Halftracks Effective and convenient long-term temporary road markers are designed to be long lasting enough for use on both low volume roads and interstate highways to provide clear guidance to motorists both night and day. Simple to install and remove.

- Two standard colors white and yellow
- Reflective tape can be applied on one or both sides
- Optional factory-applied high-tack butyl adhesive pad allows for RPM a peel and stick application to the roadway







TRPM — Flexible Chip Seal Markers

Simple to use "Stick and Stomp" TRPMs come with one or two clear plastic covers designed to protect the marker and reflective sheeting from asphalt spray or slurry products.

- Factory-applied butyl pad for reliable "Stick and Stomp" installation
- · Standard colors are yellow and white
- Available with single or double covers and multiple staple configurations
- High heat TRPMs are available for hot-applied, rubberized asphalt chip seals







TOM — Temporary Overlay Markers

Primarily for short-term temporary lane line markings in asphalt paving projects and other construction work zones, these markers are placed after final rolling of the new asphalt. TOMs are engineered for easy application and removal to reduce the amount of time workers are in the roadway.

- Standard colors are yellow and white; additional colors by special order
- · Factory-applied butyl pad keeps TOMs in place and are easily removed with a simple tug
- · Available with bright and tough cube corner, micro-prismatic sheeting on one or both sides







Curb Systems

Interstate Grade Curb (IG)

The FG 300 Interstate Grade (IG) Curb System is a lane separation system that provides efficient and cost-effective channelization of traffic on freeways, toll-ways, city streets and railhighway at-grade crossings. This one-piece curb system links together for a continuous "picket fence" effect and consists of modular raised curb sections mountable by emergency vehicles.

Testing and Certificates:

- MASH-16 certified TL3 (FHWA Letter WZ-361)
- NCHRP 350 accepted (FHWA Letter WZ-193)
- MUTCD compliant



Turnpike Grade Curb (TG)

The FG 300 Turnpike Grade (TG) curb system is a raised lane separator with durable upright channelizer posts that provide efficient and cost effective channelization of traffic on Managed Lanes, 2-way 2-lane Work Zones and other areas where discontinuous channelization is desired. Use where pavement markings alone are not sufficient to safely channelize traffic.

Testing and Certificates:

- MASH-16 certified TL3 (FHWA Letter WZ-362)
- · NCHRP 350 accepted (FHWA Letter WZ-282)
- MUTCD compliant

Surface Mount Channelizer Posts

The curving of the sides of the FG 300 tube changes the moment of inertia and builds up tremendous potential energy, resulting in a quick and sharp rebound after impact.

Testing and Certificates:

- · Proven durability on the NTPEP and TTI test decks
- NTPEP Reports #TTCD 6020.1 and 6021.11
- EN 12767 Passive Safety Certified
- MASH compliant
- MUTCD compliant
- · NCHRP 350 accepted


Round

- · Provides 360 degrees of highly reflective delineation
- · Impact resistant from all directions





- · MUTCD and NCHRP 350 compliant



These drivable flexible guide posts for roadside delineation are made of recycled engineering polymers to withstand repeated impacts.

Testing and Certificates:

- NTPEP tested (NTPEP Report 96-124)
- NCHRP 350 accepted (FHWA) Letter SS-71)
- MASH compliant
- MUTCD compliant





Poletector 360

Poletectors are highly visible and offer impact and fade resistance. They are made with durable polypropylene and snaps around new or existing cement light pole bases in minutes without the use of tools. Made in the USA.







Foam inserts provide impact resisance while keeping Poletector snug on pole.



Bollard Post Guard

Post Guard is a protective sleeve that easily fits over posts. It saves time and costs by eliminating constant scraping and repainting. The plastic part contains ultraviolet and anti-static additives that withstand extreme temperatures. Custom colors, symbols and company logos are available.

Post Guard sizes:

4.5" Dia. x 52" Square: 4.5" Dia. x 64" 4.5" x 4.5" x 55" 7" Dia. x 60" 6.5" x 6.5" x 55" 7" Dia. x 72" 8-7/8" Dia. x 72"

Easily trimmed on-site to fit your applications







EZ See Hydrant Marker

| Item # | Description |
|--------|---------------------------------------|
| 41610 | 1/4" x 4' Orange Hydrant Marker |
| 42610 | 1/4" x 4' White Hydrant Marker |
| 51610 | 1/4" x 5' Orange Hydrant Marker |
| 52610 | 1/4" x 5' White Hydrant Marker |
| 72610 | 3/8" x 5' White Hydrant Marker |
| 10501 | Bracket, Flat (hydrants) |
| 10701 | Bracket, L shaped, two 5/16" holes |
| 10801 | Bracket, L shaped, two 5/8" holes |
| | |



Driveway Marker

Item # Description

55950 5/16" x 4' Driveway Marker 55952 5/16" x 5' Driveway Marker 55962 5/16" x 6' Driveway Marker

- 5" reflective tape
- · Vinyl caps standard
- Metal caps upon request at additional cost



Parking Lot Safety

Car Stops



- Use in parking lots and garages protects garage walls, delineates spaces
- · Available in 6 ft., 4 ft. and 3 ft. lengths
- · Maintenance Free
- High visibility at night reflective stripes in yellow or white
- · Made in the USA
- · Hardware sold separately

Speed Bumps



Standard Speed Bumps

- · available in 4 foot and 6 foot lengths
- · use in moderate traffic areas
- · Available with or without reflective stripes
- 6' L 3 reflective stripes in yellow
 4' L 2 reflective stripes in yellow
- add cat eye reflectors for increased visibility

6'L — 8 cat eyes, 4'L — 6 cat eyes

- · designed for up to 10 mph
- dual bottom channels for drainage protects wire, hose, or pipe to 3/4" dia.
- · asphalt or concrete installation
- · cut with a utility knife if necessary
- · end caps sold separately

Comes with 8 Cat Eye Reflectors

Premium Speed Bumps

- · use in heavy traffic areas
- textured, vulcanized rubber performs well in extreme temperatures
- · for traffic speeds 10 mph or less
- 8 cat eye reflectors included for increased visibility at night
- 5 synthetic rubber yellow stripes, (EPDM) won't degrade
- dual bottom channels for drainage protects wire, hose, or pipe to 3/4" dia.
 Sold in 6 foot lengths, end caps sold separately

Speed Humps

- install on asphalt or concrete (hardware sold separately)
- available in 24" sections male and female end caps
- · for traffic speeds 15 mph or less
- gentler than speed bumps good for heavy traffic areas
- reflective stripes in yellow molded in marking tape
- dual bottom channels for drainage protects wire, hose, or pipe to 3/4" diameter



Channeled Plastic Parking Block



| Item Number | Wt. | Description |
|---|-----|----------------------------------|
| ULTRA3648PB | 10 | 31/4"H x 6"W x 4'L Parking Block |
| ULTRA3672PB | 15 | 31/4"H x 6"W x 6'L Parking Block |
| ULTRA4648PB | 14 | 4"H x 6"W x 4'L Parking Block |
| ULTRA4672PB | 21 | 4"H x 6"W x 6'L Parking Block |
| Available Colors: Yellow, Grey, White, and Blue | | |



Electric Vehicle Parking Block

ULTRA3672PBGN3 1/4" Ultra 6' Parking Block - Electric Vehicle Green

ULTRA4672PBGN

4" Ultra 6' Parking Block -Electric Vehicle Green



- · Maintenance Free
- · Light Weight Yet Stable
- · Chemical & Weather Resistant
- 100% Recycled Material
- Lifetime Warranty

Manufactured from Recycled Plastics







PARKING BLOCK HARDWARE Asphalt Only: ½"Wx12"Lx1 1/8" head, premium Zinc Plated Spike Asphalt and Concrete:

½"Wx5"L Premium Zinc Plated Spike Lag Bolt, Shield and Two Washers

Channeled Plastic Speed Bump



- Easy Installation
- · Virtually Indestructible
- · UV Stabilized
- · Maintenance Free
- · Light Weight Yet Stable
- · Chemical & Weather Resistant
- 100% Recycled Material
- · Lifetime Warranty



SPEED BUMP HARDWARE Asphalt Only :

½"Wx12"Lx1 1/8" head, premium Zinc Plated Spike Asphalt and Concrete: ½"Wx5"L Premium Zinc

Plated Spike Lag Bolt, Shield and Two Washers



Manufactured from Recycled Plastics



| Standard Item Number | Wt. | Description |
|----------------------|-----|--|
| 21048SBY | 14 | 2"H x 10"W x 48"L Speed Bumpw/Channels-Yellow |
| 21072SBY | 23 | 2"H x 10"W x 72"L Speed Bumpw/Channels-Yellow |
| 21096SBY | 31 | 2"H x 10"W x 96"L Speed Bumpw/Channels-Yellow |
| 210108SBY | 36 | 2"H x 10"W x 108"L Speed Bumpw/Channels-Yellow |
| 210120SBY | 43 | 2"H x 10"W x 120"L Speed Bumpw/Channels-Yellow |
| 210144SBY | 52 | 2"H x 10"W x 144"L Speed Bumpw/Channels-Yellow |
| Deluxe Item Number | | |
| 21248SBY | 17 | 2"H x 12"W x 48"L Speed Bumpw/Channels-Yellow |
| 21272SBY | 36 | 2"H x 12"W x 72"L Speed Bumpw/Channels-Yellow |

Good Seal Products/Crafco Equipment

Good Seal Products is a division of Sherwin Industries Inc., and has been manufacturing top quality, High Performance STAR SEAL BRAND sealcoats since 1981. Asphalt Emulsion, and low PAH sealcoats such as our Triton Sealers consistently out performs our competition. All our sealcoats are manufactured at our Milwaukee, WI location, where bulk pick up is available. It is also distributed to our warehouse/satellite locations throughout the state.



Brian Krawczyk - Manager

Office: (414) 281-6400 Fax: (414) 431-6550

Service Technicians

Ryan Miller Jacob Sorvala

Mike Baier - Sales Representative

Email: mbaier@sherwinindustries.com

Office: (414) 405-6511 Fax: (414) 281-6404





Sherwin Industries opened an additional location in Waterford in 2019. This location inventories most of our product line, including but not limited to, bulk sealer, pail material, and many sundry items. This location is conveniently located right off HWY 36 and Kramer Rd.

The Waterford location also serves as a U-Haul Dealer and tire shop.

Both Waterford and Milwaukee locations have a full service equipment repair department.

Phone: 800-525-8876 • Fax: 414-281-6404



Functionally Meets and/or Exceeds ASTM and FAA Specifications

Does Not Contain Coal Tar

STAR-Triton is part of a new generation of pavement sealcoatings that are high performance, effective alternatives, to both refined tar and asphalt emulsion sealers.

Based on carefully selected grades of petroleum resins, minerals, specialty additives and performance boosters, STAR-TRITON® has an extraordinary degree of toughness and water repellency, unmatched by any competitive sealer. STAR-TRITON® forms a tough, durable and flexible coating that protects asphalt pavements from the damaging elements of weather, water penetration, de-icing salts, traffic damage, surface raveling/checking, gasoline and other petrochemicals.

STAR-Triton is recommended for all asphalt pavements; home driveways, commercial parking lots, apartment complexes, restaurants, schools, gas stations, truck terminals, airfields/taxiways/airport shoulders, and many more.



STAR MICRO-PAVE PROBLEND® ASPHALT EMULSION SEALER FORTIFIED WITH RUBBER



- · Fills and smooths pavement voids
- Seals out water and sunlight
- · Seals in asphalt oils
- · Restores rich, black color
- · Provides a tough, resilient wearing surface
- Non-tracking
- · Non-toxic to workers and environment
- · Easy to clean, stripe and maintain
- · Cost effective

Macro-Flex

Based on acrylolitrile/butadince rubber.

- True rubberizing, A/B (Acrylonitrile/Butadiene) latex based additive that significantly improves the performance of Refined Tar (RTS) based sealcoatings.
- Improves toughness, flexibility and durability of the sealer.
- Increases sand/aggregate suspension and durability of the sealer.
- Improved gasoline, oil and other petro-chemcial resistance.
- · Improves color uniformity.
- Improves drying time, especially under unfavorable weather conditions.
- Not recommended for Asphalt Emulsion based sealcoatings.

| Part # | Description |
|--------|-------------|
| G1083R | 2 gallons |
| G1083 | 5 gallons |
| G1083A | 55 gallons |



Macro-Fast

Based on acrylic co-polymers, fast evaporating solvents and specialty chemicals.

- Designed for both refined tar and asphalt emulsion based sealers.
- Faster drying time, reduced by up to 50%.
- Does not increase the viscosity of the sealer.
- Reduces marking and tracking.

| Part # | Description |
|--------|-------------|
| G1084 | 5 gallons |



Advantage-4

High Potency Additive, based on 100% acrylics, water repellents, and color stabilizers.



- Designed for both refined tar and asphalt emulsion based sealers.
- Significantly reduces drying times.
- Performance boosting (higher scuff and chemical resistance).
- Improves color retentions, sealer dries jet black and stays that way.
- Increases viscosity for improved sand/aggregate suspension.

Part # Description G1086 5 gallons

Phone: 800-525-8876 • Fax: 414-281-6404

STAR Spectrum

Colorized Acrylic Pavement Sealer

Excellent durability! Spectrum® has been proven as a viable alternative to many traditional pavement coating products.



- A Bright New Product That Protects, Beautifies And Extends The Life Of Your Asphalt Pavement.
- Magnificent color that protects asphalt and concrete surfaces! Spectrum[®] cures to a vibrant color that will resist fading and weathering with time.



Simply Brilliant!

SPECTRUM BRIGHTS SPECTRUM STANDARDS SPECTRUM NATURALS LILY WHITE SKY BLUE SAGE GREEN Pure Titanium White Similar to Pantone 632 Blue Similar to Pantone 349 Green LEMON YELLOW SEA FOAM GREEN BRICK RED Similar to Pantone 395 Yellow Similar to Pantone 326 Green Similar to Pantone 180 Red **BIKE LANE GREEN** FAIRWAY GREEN DARK GRAY Similar to Pantone 375 Green Similar to Pantone 364 Green Similar to Pantone 430 Gray OCEAN BLUE SALMON ORANGE SAHARA TAN Similar to Pantone 300 Blue Similar to Pantone 165 Orange Similar to Pantone 728 Brown CONCORD PURPLE LIGHT BROWN MAGENTA Similar to Pantone Violet Similar to Pantone 207 Red Similar to Pantone 477 Brown PEPPERMINT PINK COOL GRAY SUEDE BROWN Similar to Pantone 205 Pink Similar to Pantone 6 Cool Gray Similar to Pantone 7610 Brown HOT ROD RED STANDARD BLACK CUSTOM COLOR MIX Similar to Pantone 711 Red Dries to a Rich Black Color Custom Colors are Available

SOS Primer

Dries clear, water-based.

- A strong bonding primer for asphalt (Seals oil, grease, fuel, etc.).
- Dries quickly, in approximately 20-30 minutes.
- · Water based for easy clean-up.
- Supplied in a concentrate form, must be diluted 1 part SOS with 2 parts water.

Part # Description
G1087B 1 gallon
G1087 5 gallons





Sta-Flex

Standard grade, water based, cold-pour crack filler.

- · Rubberized crack filler with polymers.
- Cold-applied and ready to use, no heating is required.
- Protects against water and salt penetration.
- Safe to use and store, non-flammable, cleans up with water.

Coverage: 100 linear feet @

(3/8" wide by 1/2" deep)

Part # Description
G1092 1 gallon
G1093 5 gallons





STAR Genesis

Specialty water based primer & sealer, dries black.

- As a Coating will prevent oil, grease and contaminants from penetrating into the asphalt pavement
- As a Primer will prevent oil, grease and contaminants from bleeding up through the seal coating, and will improve surface appearance.

Part # Description G1097 5 gallons



Sta-Flex Trowel Grade

Trowel grade patching compound, water based, cold-applied.

- Heavy bodied for cracks over 3/4" wide.
- Superior grip with high elasticity.
- · Easily trowel-able into cracks.
- Cold-applied and ready to use, no heating is required.
- Safe to use and store, non-flammable, cleans up with water.

Coverage: Varies greatly depending on

application. (approx.1 gallon per 25 sq.ft.)

Description

Part # Description

G1094 1 gallon G1095 5 gallons





SURFIX Premium

- Heavy bodied mastic patching & repair product designed for excessively cracked areas
- Outstanding flexibility and toughness resulting into superior performance
- Compatible with both coal tar and asphalt emulsion sealers.
- Cleans up with water

Coverage: Varies greatly depending

on application. (approx. 1 gallon per 25 sq ft)

Part # Description G1040 5 gallons





Star Macro-Deck

STAR MACRO-DECK® stops water, chloride de-icing chemicals, salt, and other damaging elements from entering the concrete surface. Specifically developed to protect concrete structures; bridge decks, superstructures, and control barriers.

- DOT approved in many states.
- Improves the tensile and flexural strength of concrete.
- Easy to apply and store.
- Safe to handle, non-flammable, and non hazardous.

SSMD5 5 gallon pail **SSMD55** 55 gallon drum



Star Armour Guard

STAR® ARMOUR-GUARD™ is a residential grade penetrant and sealant. It is a specialty clear penetrating sealer that was developed to protect and improve the performance of common building materials such as; concrete, brick, masonry and more.

- Slows the degradation caused by de-icing salts and chemicals.
- Easy to apply with water like consistency and fluidity.
- Safe to handle, non-flammable, and non hazardous.

SSCA5 5 gallon pail SSCA55 55 gallon drum SSCA275 275 gallon tote



DecoColor®

| G1210 | Ready to Use Color Coating Blue | 5 gal. pail | G1233 | Custom Coating | |
|-------|----------------------------------|-------------|--------|--|--------------|
| G1211 | Ready to Use Color Coating Red | 5 gal.pail | | Concentrated Summer Red | 55 gal. drum |
| G1212 | Ready to Use Color Coating Green | 5 gal. pail | G1234 | Custom Coating | |
| G1213 | Ready to Use Color Coating Tan | 5 gal. pail | | Concentrated Spring Green | 55 gal. drum |
| G1236 | Custom Coating | | G1250 | Acrylic Base for Recreational Surfaces | 55 gal. drum |
| | Concentrated Forest Green | 55 gal drum | G1250A | Acrylic Base for Recreational Surfaces | 5 gal. pail |

DecoTurf provides the world's best acrylic surfaces. Professional and residential customers alike consistently choose our sports courts for tennis surfaces, basketball court surfaces, hockey surfaces and other projects where a reliable and consistent playing system is required. View our project gallery to see real life application of our products and colors. TENNIS BASKETBALL MULTI-SPORT DECORATIVE

Aquaphalt

Revolutionary permanent asphalt and concrete repair material for pothole repair, pavement repair, utility cuts, walkways, tennis courts and driveway repair — it works even in wet and cold conditions.

- Eco-friendly binder reacts and hardens with only water no toxic solvents
- Aquaphalt is laid directly from its container—no need to mobilize large crews and equipment
- Minimizes roadway disruption with no need for special preparations
- Pre-mixed and permanent Aquaphalt is a one-time fix









Silica Sand



Part # G1116

Description50# bags
Medium #4020
70 bags per pallet

Black Boiler Slag

Part # G1117A G1117 G1117B

#3060 Finest #2040 Fine #1240 Coarse

Description 100# bags 40 bags per pallet



Rock Salt

G1301



50 lb bag Calcium Chloride pallet (56 bags)

G1300



50 lb bag Ice Melt pallet (49 bags)

Cold Patch

***S10A** Cold Patch 5 gallon pail ***S10** Cold Patch Bulk



Miscellaneous Sealing Tools

| PART # | DESCRIPTION |
|--------|---|
| G1130 | 18" Sealer Brush with Handle |
| G1131 | 18" Sealer Brush Refill |
| G1134 | 24" Heavy Duty Sealer Brush with Handle |
| G1135 | 24" Heavy Duty Sealer Brush Refill |
| G1136 | 36" Heavy Duty Sealer Brush with Handle |
| G1137 | 36" Heavy Duty Sealer Brush Refill |
| G1137A | 48" Heavy Duty Sealer Brush |
| G1137B | 48" Heavy Duty Sealer Brush Refill |
| G1138 | 12" Throw-Away Sealer Brush/Squeegee |
| G1138A | 48" Throw-Away Sealer Brush Handle |
| G1141 | 18" Throw-Away Sealer Brush /Squeegee |
| G1145A | Aluminum Holder for Brushes |
| G1145B | 3-1/4" Aluminum Brush Bracket (smaller) |
| G1190 | 5" Wide Brushes for Sealing Machine |
| G1176 | 3" Scraper (handle sold separately) |
| G1180 | Rubber Sealing Gloves |
| G1141A | Sealer Broom with Handle |
| G1141B | 24" Sealer Broom Head |
| G1141C | 36" Sealer Broom Head |
| G1158 | Bracket for Broom Handle |
| G1142 | 30" Heavy Duty Squeegee with Handle |
| G1142A | 30" Squeegee Refill |
| G1143 | 36" Heavy Duty Squeegee with Handle |
| G1143A | 36" Heavy Duty Squeegee Refill |
| G1144 | 60" Heavy Duty Squeegee with Steel Frame |
| G1144A | 5" Squeegee Refill Punched |
| G1145 | Aluminum Squeegee Holder |
| G1160A | 8' Wooden Handle |
| G1160 | 6' Wooden Handle |
| G1170 | Drum Mixer for 1/2" Drill |
| G1171 | 5 Gallon Pail Mixer for 1/2" Drill |
| G1260 | 5 Gallon Plastic Pail with Cover |
| G1263 | 5 Gallon Plastic Pail Opener For Easy Lid Removal |
| G1262 | 55 Gallon Steel Drum Open Head with Cover |
| G1163 | 3" Putty Scraper |
| G1164 | Rolatape Small Style |
| G1165 | Rolatape Large Style |
| G1140 | Vandal Mark Remover, 20 oz. |
| G1140A | Big Orange Industrial Spray, 18.5 oz. |

G1206

Fuel Oil Brush











G1286

Mobile Sprayer Sealer Tank Accessories

G1280 3" Heavy Duty Rubber Discharge Hose

G1281 2" Plastic Discharge Hose

G1282 2" Heavy Duty Rubber Discharge Hose

G1283 5' Aluminum Sealer Wand with Valve Tip Included

G1283A 5' Aluminum Wand, no valve tip included G4450 Exhaust Muffler with Filter for Spray Unit G1284 3/4" High Pressure Hose 300 psi, no fittings G1284A Hose Fitting for High Pressure Hose, both ends (2) G1284B 1/2" High Pressure Hose 300 psi, no fittings G1284C 3/8" High Pressure Hose 300 psi, no fittings

coupler and 2" short nipple

G1287 6' Plastic Hose (2") 1" quick coupler on one end and 2" short nipple

2" Ball Valve, 6\' Plastic Hose (2"), 1 set of quick

G1161 Steel Spray Tip 80/40 Steel Spray Tip 80/50 G1161A G1161C Steel Spray Tip 80/70 G1161D Steel Spray Tip 80/100

G1167 2" heavy Duty Brass Ball Valve

G1167A 3/4" Brass Ball Valve G1167B 1/2" Brass Ball Valve G1172 Spray Wand Reducing Bushing, 3/4" pipe to 1/4"

Spray Wand Reducing Bushing, 3/4" pipe to 3/8" G1172A Spray Wand Reducing Bushing, 3/4" pipe to 1/2" G1172B G1173 2" Quick Coupler - aluminum, female and female ends G1173A 2" Quick Coupler - aluminum, male end with female thread

G1173B 2" Quick Coupler Casing Nipple









Safety Products



Safety Glasses: Fashionable and safe all at the same time! A must have for cleaning crews



Caution and Banner Tape: Caution tape comes in 1000' rolls. Banner tape in 300' rolls



Disposable Coveralls & Pants: The inexpensive way to keep your clothing clean. Sturdy enough to get several uses before replacing.

Little Wonder® High Output Blowers

Little Wonder is the industry leader in debris management equipment, utilizing air power to move or collect debris.

Little Wonder blowers lead the industry in air power, unit construction, ease of operation and user comfort.

We have a blower to meet your needs and exceed your expectations.







C5 Blower

- The power to blow heavy, wet leaves faster
- Adjustable handle with padded grips for comfort
- Wheels designed for stability over rolling terrains and slopes
- Fold-down handles for compact storage when the work is done
- Powerful, dependable professional grade Subaru® engine
- Aim Rite[™] discharge nozzle controls air direction with tool-free adjustment



Swivel Wheel Kit (Part # 9050-00-01)

- Easy to install.
- Gives operator 360° turning control.
- Can also be locked in a straight position.

Optimax

- Advanced impeller and aerodynamic design produce the highest airflow in the industry
- Patented split-stream air deflector moves piles of leaves farther and faster; without blow-back!
- Large, square discharge chute is low to the ground for better blowing power
- Scrolled housing ensures consistent, constant airflow even if partially blocked by leave
- Continuously welded all-steel impeller and housing for strength and durability you can rely on season after season
- Remote discharge chute control on the handle at your fingertips
- Ergonomic handle design; height adjust able with anti-vibration grip
- Transport bracket for convenient tiedown during transport.
- Convenient lift handle makes lifting the blower on and off the truck easier.
- · Optional Swivel Wheel Kit for 360° turning
- · 5-Year warranty

Optimax - Self Propelled

- Self-propelled up to 4.1 mph forward and 2.5 mph reverse
- Advanced impeller and aerodynamic design produce the highest airflow in the industry
- Patented split-stream air deflector moves piles of leaves farther and faster; without blow-back!
- Large, square discharge chute is low to the ground for better blowing power
- Scrolled housing ensures consistent, constant airflow even if partially blocked by leaves
- Continuously welded all-steel impeller and housing for strength and durability you can rely on season after season
- Remote discharge chute control on the handle at your fingertips
- Ergonomic handle design; height adjust able with anti-vibration grip
- Transport bracket for convenient tiedown during transport.
- Convenient lift handle makes lifting the blower on and off the truck easier.
- Optional Swivel Wheel Kit for 360° turning
- 5-Year warranty

High Performance Vacuum

Little Wonder leaf and debris vacuums clear and collect all types of debris – large and small; bottles, cans, leaves, pine needles, straw, gravel, and other debris that would normally have to be swept up by hand.



Pro Vac Self-Propelled (Part #5612-12-01)



Pro Vac (Part #5612-00-01)

Little Wonder Edgers

The Pro Edger is user–friendly with fingertip controls and a ratchet–arm height adjustment system for fatigue–free operation and control. The Little Wonder Pro Edger is built for heavy, daily usage. Cut create crisp, distinct edges faster, and with less effort.



Little Wonder Crack Cleaner

The Pro Crack Cleaner cleans cracks and crevices in asphalt and concrete surfaces quickly and easily. Clearing away debris and undergrowth is extremely important before laying down crack filler and applying sealant. Dual belts to the brush clear crevices quicker and more thoroughly.





Phone: 800-525-8876 • Fax: 414-281-6404

Billy Goat™

F6 Small Property / Residential

Wheeled Blower 6 HP

Model #: F602V (Vanguard) F602X (Briggs & Stratton)

FEATURES

- Patented Aim N Shoot™
- 169cc commercial Vanguard engine
- · 205cc Briggs & Stratton engine
- 16" 16-blade advanced fan technology
- · Smooth rounded housing
- Optional forward discharge
- 2.3x the air volume of backpacks

F9 Large Property / Commercial Wheeled Blower 9 HP

Model #: F902H (Honda) Push model

FEATURES

- Patented Aim N Shoot™ fingertip control
- 17" 16-blade advanced fan technology
- · Low weight, low noise, ergonomic handles
- No rust, no dent composite housing (5-year warranty)
- Self-propelled option eliminates fatigue
- 3.8x the air volume of backpacks



Wheeled Blower, 13 HP

Model #: F1302H (Honda) Push model F1302SPH (Honda) Self-propelled

FEATURES

- Patented Aim N Shoot™ fingertip control
- 17" 16-blade advanced fan technology
- · Low weight, low noise, ergonomic handles
- · No rust, no dent composite housing (5-year warranty)
- Self-propelled option eliminates fatigue
- · 6.2x the air volume of backpacks

F18 The Ultimate

Wheeled Blower 18 HP

Model #: F1802V (Vanguard) F1802SPV Self-propelled

FEATURES


- Patented Aim N Shoot™ fingertip control
- 570 cc commercial engine
- 17" 16-blade fan
- · Forward discharge
- Self-propelled option
- 7x the air volume of backpacks



ONLY 89 LBS!

(F602V)





Grazor™: GZ551V

Pavement Surface Prep

FEATURES

- 169 cc Vanguard engine
- · 6-position height adjustment
- 8" steel wire brush
- · Remote brush declutch
- Heavy-duty frame and caster
- 1-vear machine. 3-year engine warranty









Sherwin Industries, Inc.

MILWAUKEE, WISCONSIN ESTABLISHED 1938



Corporate Office

2129 W. Morgan Ave., Milwaukee, Wisconsin 53221 Email: corporate@sherwinindustries.com

Local: 414-281-6400 Toll Free: 800-525-8876 Fax: 414-281-6404

Waterford Office

28020 Kramer Road, Waterford, WI 53185 Local: 262-332-6014

www.sherwinindustries.com

Good Seal Products

A Division of Sherwin Industries, Incorporated